



Engineers and Soil Scientists

Agri-Waste Technology, Inc.
501 N. Salem Street, Suite 203
Apex, North Carolina 27502
919-859-0669
www.agriwaste.com

Septic System Inspection Report

2089 Suitts Store Road Franklinton, NC

Prepared for:	Dawn Regan, Buyer
Prepared By:	Jeff Vaughan, NCOWCICB Certified Inspector Senior Agronomist/Soil Scientist
Report Date:	May 9, 2022



Agri-Waste Technology, Inc.
501 N. Salem Street, Suite 203
Apex, North Carolina 27502
919-859-0669
www.agriwaste.com

SEPTIC SYSTEM INSPECTION REPORT

For
2089 Suitts Store Road
Franklinton, NC

PREPARED FOR: Dawn Regan, Buyer

PREPARED BY: Jeff Vaughan, NCOWCICB Certified Inspector
Senior Agronomist/Soil Scientist

A handwritten signature in black ink, appearing to read 'Jeff V', located below the 'PREPARED BY' line.

DATE: May 9, 2022

The septic system serving the home at 2089 Suitts Store Road, Franklinton, NC, was inspected by McLean Davis of Agri-Waste Technology, Inc., on May 5, 2022. The septic system is a conventional gravity system with a drainfield and septic tank. The Granville County Health Department documentation for the septic system is in Attachment 1. A copy of the septic system inspection checklist completed during the May 5, 2022, inspection is in Attachment 2. A detailed discussion of the inspection is below.

General septic system information can be found on the North Carolina State University Soil Science Department website. The address is www.soil.ncsu.edu. Some routine septic system maintenance information is in Attachment 3 following this report.

Septic Drainfield

No septic effluent was found at the soil surface within the septic drainfield (Attachment 4). The drainfield is part of a wooded area. Surface water did not appear to collect anywhere within the drainfield. Vegetation should be maintained and kept maintained on a routine basis within the drainfield.

Septic Tank

The septic tank was excavated on the inlet and the outlet ends (Attachment 4). The concrete tank, inlet pipe, outlet pipe, and outlet baffle were in good condition. Root intrusion was noted within the drainfield line. The septic tank contains 0" of solids. The septic tank was pumped on 5/5/22. Attachment 3 contains a table entitled *Estimated Septic Tank Inspection and Pumping*

Frequency in Years that indicates the recommended pumping frequency based on the number of occupants in the house and the septic tank size.

Conclusions

- 1) Vegetation should be maintained and kept maintained on a routine basis within the drainfield.
- 2) Root intrusion was noted within the drainfield line.

We appreciate the opportunity to assist you. Please contact us with any questions, concerns, or comments.

As indicated in the AGREEMENT FOR PROFESSIONAL ENVIRONMENTAL SERVICES “Point of sale well/septic system inspections constitute a snapshot evaluation in time of the system(s) and do not guarantee future performance of the system(s) due to numerous factors including, but not necessarily limited to, the following: water use patterns of the inhabitants of the dwelling, occupancy of the dwelling (no occupancy for an extended period of time or occupancy in excess of the system design parameters), acts of God or natural disasters, lack of visibility of many of the system components, placement of inappropriate items into the system (non-degradable items, water softener brine, etc.), physical disturbance of or damage to the system or system components, etc. Furthermore, only the aboveground components of the well that are visible from the soil surface are inspected.”

**ATTACHMENT 1: Granville County Health Department
Documentation**



Engineers and Soil Scientists

Agri-Waste Technology, Inc.
501 N. Salem Street, Suite 203
Apex, North Carolina 27502
919-859-0669
www.agriwaste.com

To Whom It May Concern,

In response to our recent request for a copy of the Well and/or Wastewater permit serving the property located at **2089 Suitts Store Road, Franklinton, NC 27525** a file search was conducted by **Granville County** on **Wednesday, May 4, 2022**. During this file search, no such permit was located. This does not necessarily mean that no such permit was issued, but rather it was not located during the County's file search.

Thank you!

ATTACHMENT 2: Septic System Inspection Checklist

SUBSURFACE WASTEWATER SYSTEM INSPECTION REPORT

Date of Inspection		Inspector's Name		Certification Number
Permit Number		Date of Operation Permit		Advertised # of Bedrooms
Buyer		Address of Property		Current Owner
Tax Map	Parcel	Lot #	PIN	Water Source

INSPECTION RESULTS:

<u>COLLECTION/TANK SYSTEM:</u>	YES	/	NO	/	NA	<u>REMARKS</u>
Evidence of leaks ?	☐	/	☐	/	☐	
Water level in tank: _____						
Tank risers accessible, free of infiltration and surface water diverted ?						
Inlet riser?	☐	/	☐	/	☐	
Type: _____						
Outlet riser?	☐	/	☐	/	☐	
Type: _____						
Estimated distance from soil surface to Top of tank: _____ inches						
Tank has baffle wall?	☐	/	☐	/	☐	
Outlet T is present/intact?	☐	/	☐	/	☐	
Roots present in tank?	☐	/	☐	/	☐	
Inlet pipe clear/unobstructed?	☐	/	☐	/	☐	
Outlet pipe clear/unobstructed?	☐	/	☐	/	☐	
Septic tank needs pumping?	☐	/	☐	/	☐	
Inches of solids: _____						
Date of last tank pumping known?	☐	/	☐	/	☐	
If known, when: _____ / _____ / _____						
Estimated Distance From:						
House/Structure: _____ ft						
Well: _____ ft						
Water Line: _____ ft						
Property Line: _____ ft						
Septic tank filter cleaned?	☐	/	☐	/	☐	

PRETREATMENT SYSTEM:

(Sand Filter or Peat Biofilter)					
Certified operator required?	☐	/	☐	/	☐
Filter surface maintained ?	☐	/	☐	/	☐
Evidence of ponding ?	☐	/	☐	/	☐
Filter effluent free of excess solids ?	☐	/	☐	/	☐
Peat modules free of damage, accessible, properly ventilated & free of insects ?	☐	/	☐	/	☐
Samples collected at this inspection ?	☐	/	☐	/	☐

EFFLUENT DOSING SYSTEM:

Required pumps present & functional ?	☐	/	☐	/	☐
High water alarm operating properly ?	☐	/	☐	/	☐
Floats, valves, etc. in good condition ?	☐	/	☐	/	☐
Control panel & components in good condition ?	☐	/	☐	/	☐
Evidence of leaks ?	☐	/	☐	/	☐
Water level in tank: _____					
Tank riser accessible, free of infiltration and surface water diverted ?	☐	/	☐	/	☐
Type: _____					
Roots present in tank?	☐	/	☐	/	☐
Estimated distance from soil surface to Top of tank: _____ inches					

Date of last tank pumping known? ☐ / ☐ / ☐

If known, when: ____/____/____

Estimated Distance From:

House/Structure: ____ ft

Well: ____ ft

Water Line: ____ ft

Property Line: ____ ft

Septic Tank: ____ ft

Effluent free of excess solids ? ☐ / ☐ / ☐

Inches of solids(pump/dose tank): _____

Elapsed time readings ? _____

Counter readings ? _____

DISPOSAL FIELD:

Evidence of effluent surfacing ? ☐ / ☐ / ☐

Evidence of effluent ponding in trenches? ☐ / ☐ / ☐

Surface water effectively diverted ? ☐ / ☐ / ☐

Diversions/swales properly maintained ? ☐ / ☐ / ☐

Vegetative cover maintained ? ☐ / ☐ / ☐

Protected from traffic/unauthorized uses ? ☐ / ☐ / ☐

Distribution devices in good condition ? ☐ / ☐ / ☐

Field free of settled or low areas ? ☐ / ☐ / ☐

Estimated Distance From:

House/Structure: ____ ft

Well: ____ ft

Water Line: ____ ft

Property Line: ____ ft

Septic Tank: ____ ft

PRESSURE DISTRIBUTION SYSTEM:

Certified operator required? ☐ / ☐ / ☐

Turnups/cleanouts/valves intact &

accessible ? ☐ / ☐ / ☐

Laterals free of excess solids ? ☐ / ☐ / ☐

Laterals flushed this inspection ? ☐ / ☐ / ☐

Pressure heads properly adjusted ? ☐ / ☐ / ☐

SYSTEM PERFORMANCE:

Design Pressure Head (ft): _____ Adjusted Pressure Head (ft): _____

Design Delivery Rate (gpm): _____ Measured Delivery Rate (gpm): _____ % of Design: _____

Dosing Volume (gal.): _____

Note: Delivery Rate(gpm) = (_____ inches drawdown _____ gallons/in) _____ minutes of run time

Dose Volume(gal.) = _____ inches between float on & float off _____ gallons/in.

“Client requesting this inspection has been advised that for a complete inspection to be performed, the tank needs to be pumped. Client has declined to have the tank pumped at inspection and hereby acknowledges they have so declined.”

Signature

ADDITIONAL COMMENTS:

Jasmine Lott

From: info@agriwaste.com on behalf of Agriwaste <info@agriwaste.com>
Sent: Monday, May 2, 2022 4:13 PM
To: Info
Subject: New submission from Inspection Service 2.0

Who Are You?

Who are you?

Home Buyer

Inspection Type?

Inspection Type?

Both Septic & Well

Your Information

Name

Dawn Regan

Address

5534 E. Granger Street
Inverness, Florida 34452
United States
[Map It](#)

Phone

(352) 422-6129

Email

dawneregan@gmail.com

Send a Copy to Your Real Estate Agent?

Send a copy to your Real Estate Agent?

No Thanks

Property Information

Property Address

2089 Suitts Store Road
Franklinton, North Carolina 27525
United States
[Map It](#)

Subdivision Name & Lot Number

Unknown

County

Granville

Year house was built?

1988
How many bedrooms does the house have?
3
Current owner's name?
Gerald Conrad
Will anyone meet AWT during the inspection?
Yes
Who will meet AWT?
Keith and/or Judy Johnson
Is the property occupied?
No
Is power/water on?
Yes
Is property under HUD/VA/FHA/USDA loan?
No
Do you have a copy of the Septic Permit?
No
Pricing
Well Inspection/Lab Analysis DURING THE SAME VISIT with a Septic Inspection (price added onto septic inspection cost below)
\$160.00 - FHA/VA/HUD - Full Panel (coliform bacterial analysis, lead, nitrate, nitrite) (7 business days)
Contract Authorization
Contract Authorization
I elect to have the septic tank pumped as part of the inspection. AWT will coordinate the pumping service and the fee will be added onto the final inspection invoice. The pumping cost \$350 (for each septic tank) depending on the location of the inspection. This fee is in addition to the inspection costs detailed above. I understand that If I cancel within 48 hours of the scheduled inspection and have elected to have the septic tank pumped I will be charged \$150.00. Please call for any questions or clarification on the policy.
Authorized Representative Signature
Dawn Regan
Date
05/02/2022
Any Additional Comments?
Additional Comments
Please mark where tank and field are located
Contract Authorization
I agree to the above contract

- I agree to the above contract

Inspection Consent

I/We the potential buyers (or buyers representative) have obtained written permission from the current homeowner(s) to complete the septic system inspection.

AGREEMENT FOR PROFESSIONAL ENVIRONMENTAL SERVICES

This Agreement for Professional Environmental Services (Agreement) made and entered into on 05/02/2022 by and between **Dawn Regan** (hereinafter referred to as "Client") located at **5534 E. Granger Street , Inverness, Florida 34452, (352) 422-6129, dawneregans@gmail.com** and AGRI-WASTE TECHNOLOGY, INC., a North Carolina corporation, having its principal place of business located at 501 N. Salem Street, Suite 203, Apex, NC 27502, (919) 859-0669 (hereinafter referred to as "AWT").

RECITALS:

WHEREAS, Client is desirous of entering into a contract with AWT and AWT is desirous of entering into a contract with Client to perform professional environmental services (the "Services") for a property or facility located at various client sites covering the whole United States and foreign countries ("Site"), upon the terms and subject to the conditions hereinafter set forth; and

WHEREAS, AWT is engaged in the business of providing such professional environmental services.

NOW, THEREFORE, in consideration of the mutual covenants and agreements contained herein, and for such other good and valuable consideration, the receipt and adequacy of which are hereby admitted and acknowledged, the parties hereto agree as follows:

1.0 Retention of Professional Services.

AWT shall perform the Services specified in Attachment A to this Agreement, which is incorporated herein by reference. The Services shall be performed as described in Attachment A, and in accordance with the terms of this Agreement.

2.0 Term.

The term of this Agreement shall commence as of the date of this Agreement and continue from time to time thereafter, subject to a right of the parties to terminate such Agreement as provided in Section 14.0 herein.

3.0 Compensation.

3.1 AWT shall receive compensation and Client shall pay AWT for the Services and expenses incurred in accordance with the payment schedule specified in the Scope of Services, which is incorporated herein by reference. Each invoice, on presentation, is due and payable by Client. Invoices are past due after 10 days. Past due amounts are subject to a service charge of one and a half per cent per month (18 percent per annum) on the outstanding balance. Attorney's fees and other costs incurred in collecting past due amounts shall be paid by Client.

3.2 The terms of this Agreement do not in any way relieve Client from the obligation to pay for services rendered for Client by AWT under another agreement or any additional services as specifically authorized by Client in excess of those stated in this Agreement.

3.3 The Client's obligation to pay for the Services contracted for is in no way dependent upon the Client's ability to obtain financing.

3.4 Unless specified otherwise, all payments received from Client shall be applied to the most outstanding account balance.

4.0 Warranties of AWT.

AWT represents and warrants as follows:

4.1 That AWT has full right and power to enter into and fully perform this Agreement.

4.2 That AWT is or intends to be engaged in like or similar Agreements with other parties.

4.3 That AWT will perform the Services for Client in a professional manner, using that degree of care and skill ordinarily exercised by and consistent with the standards of competent consultants practicing in the same or similar locality as the Project.

4.4 That each of the AWT personnel assigned to undertake the Services under this Agreement is professionally qualified to undertake such Services, and has received all applicable and appropriate certifications and licenses required to perform such Services.

4.5 That AWT will provide supervisory and other appropriate personnel with adequate experience with planning and engineering services to make professional judgements concerning the adequacy of the Services.

4.6 That AWT will, to the maximum extent reasonably possible, make all efforts to ensure the continuity of AWT personnel assigned to this project.

5.0 Warranties of Client.

Client represents and warrants as follows:

5.1 That Client has full right and power to enter into and fully perform this Agreement.

5.2 That all information provided by Client to AWT regarding the Site and Services are complete and accurate to the best of Client's knowledge.

5.3 That Client owns or controls the Site, or has otherwise been granted access to the Site by the party that owns or controls the Site. If Client owns or controls the Site, Client agrees to furnish AWT and its agents and subcontractors a right-of-entry onto the Site and permission to perform the Services. If the Site is not owned or controlled by Client, Client represents and warrants that it has fully disclosed to AWT the conditions imposed on access to the Site by the party which owns or controls the Site.

5.4 That AWT has fully described the risks and limitations associated with the Services, including the risks and limitations associated with the review of available records, visual inspections, and sampling and analytical techniques which AWT will use to perform the Services, and that Client fully understands such risks and limitations, and that Client has engaged AWT to undertake the services described herein with such understanding.

5.5 That sufficient funds are available or will be available upon receipt of AWT's invoice to make payment in full for the Services.

5.6 That neither AWT nor any of AWT's consultants or subcontractors has offered any fiduciary service to Client and no fiduciary responsibility shall be owed to Client by AWT or any of AWT's subconsultants or subcontractors, as a consequence of AWT's entering into this Agreement with Client.

6.0 Protection Against Disclosure of Confidential Information.

6.1 AWT shall not directly or indirectly disclose or use at any time, either during or subsequent to this Agreement, any secret or confidential information provided to AWT by Client during the term of this Agreement unless (a) such disclosure or use is authorized by this Agreement, (b) such information is otherwise publicly available, or (c) AWT receives written consent by Client to so disclose or use such information.

6.2 Disclosure by AWT of any confidential information to any party designated by Client to receive such information shall not constitute a breach of this Agreement.

7.0 Reports.

7.1 In connection with the performance of the Services, AWT shall deliver to Client, or to any other party which Client designates, one or more reports or other written documents reflecting the Services provided, the results of such Services and AWT's evaluation of the results of such Services.

7.2 All drafts and final versions of all reports and written documents delivered to Client are instruments reflecting the services provided by AWT pursuant to this Agreement and are made available for Client's use subject to the limitations of this Agreement.

7.3 The Services, and any data, recommendations, proposals, reports, design criteria, and similar information provided by AWT to Client pursuant to this Agreement are provided for the exclusive use of Client regarding the Site, and are not to be used or relied upon in connection with other projects or by third parties. Computer disks, computer files or data on computers or disks are the property of AWT are not deliverable products or services, unless specifically identified in the attached Scope of Work.

8.0 Safety.

With respect to the performance of the Services, AWT shall take safety precautions required by federal, state and local laws, rules, regulations, statutes or ordinances. AWT shall abide Client's safety rules to the extent that Client informs AWT of such rules. If Client conducts activities at the Site at any time scheduled by AWT to undertake Services at the Site, AWT shall not be responsible for Site safety, and shall have neither the right nor the obligation to direct or stop the work of Client's contractors, agents, or employees.

9.0 Samples.

9.1 Unless otherwise requested, test specimens, or samples will be disposed of immediately upon completion of tests and analysis. Upon written request, AWT will retain samples for a mutually acceptable storage charge and period of time.

9.2 In the event that samples contain or may contain Hazardous Substances, AWT shall, after completion of testing and at Client's expense, (a) return such samples to Client or project site, or (b) using a manifest signed by Client as a generator, have such samples transported to a location selected by Client for final disposal. For purposes of this Agreement, the term Hazardous Substances shall be defined as that term is defined by the Federal Comprehensive Environmental Response, Compensation and Liability Act of 1980, as amended, 42 U.S.C. 9601 (14). Client recognizes and agrees that AWT is acting as a bailee and at no time assumes title to said samples.

10.0 Title to Waste.

AWT shall not acquire any property interest in any materials containing Hazardous Substances that are removed from the Site by AWT or any subcontractor of AWT, or are in any way associated with Services at the Site performed by AWT or any subcontractor of AWT.

11.0 Project Site.

11.1 AWT will take reasonable precautions at the Site to minimize damage to the Site from the Services performed by AWT. Client recognizes that the performance of the Services may cause alteration or damage to the Site, and that such alteration or damage is inherent to the performance of the Services. Absent negligence for which AWT, its agents or subcontractors is solely responsible, or an intentional act by AWT, its agents or subcontractors beyond the scope of the Services, Client waives any right to seek reimbursement from AWT or otherwise to hold, or seek to hold, AWT liable or responsible for any such exclusive property of AWT.

11.2 If Client does not own the Site, Client agrees to notify the owner and any operators of the Site of the aforementioned possibility of unavoidable alteration and damage.

11.3 Client agrees to disclose the identity of all utilities serving the Project Site and the presence and accurate location of hidden or obscure man-made objects relative to field tests or boring locations of which it knows or has reason to know.

11.4 AWT will not be liable for damage or injury to subterranean structures (pipes, tanks, telephone cables, etc.) arising from the performance of AWT's services when the existence of such subterranean structures are known or reasonably should be known by Client and are not called to AWT's attention by Client, or when the location of such subterranean structures is incorrectly shown or described in the information furnished to AWT.

12.0 Independent Contractor.

12.1. The parties acknowledge that nothing contained in this Agreement shall create an employer-employee, joint venture, agency, or other relationship between AWT and Client. The parties acknowledge that AWT is acting as an "independent contractor."

12.2. Neither party's employees or agents are authorized to represent the other party or to make commitments in any form whatsoever on behalf of the other party unless expressly authorized by this Agreement or in a separate writing signed by the other party.

13.0 Termination of Contract.

This Agreement may be terminated by either party upon seven days' written notice in the event of substantial failure by the other party to perform in accordance with the terms hereof. Such notice shall specify a reasonable period of time to cure the alleged substantial failure to perform in accordance with the terms hereof. Such termination shall not be

effective if that substantial failure has been cured before expiration of the period specified in the written notice. In the event of termination, AWT shall be paid for Services performed to the termination date plus reasonable termination expenses.

14.0 Unforeseen Occurrences.

If during the performance of services hereunder, any unforeseen Hazardous Substance, conditions or occurrences are encountered which, in AWT's sole judgment, significantly affect or may affect the Services, the risk involved in providing the Services, or the recommended scope of Services, AWT will promptly stop that portion of the work and notify Client thereof. Subsequent to that notification, AWT may:

(A) If practicable, in AWT's sole judgment and with approval of Client, complete the original scope of Services in accordance with the procedures originally intended in the Proposal;

(B) Agree with Client to modify the scope of Services and the estimate of charges to include study of the previously unforeseen conditions or occurrences, such revision to be in writing and signed by the parties and incorporated herein; or

(C) Terminate the services effective on the date of notification pursuant to the terms of Section 14.0 herein.

15.0 Force Majeure.

Should completion of any portion of the Services be delayed for causes beyond the control of, or without the fault or negligence of AWT, including force majeure, the time for performance shall be extended for a period equal to the delay and the parties shall mutually agree on the terms and conditions upon which the Services may be continued. Force majeure includes, but is not restricted to, acts of God or the public enemy, acts of the Government of the United States or of the several states, or any foreign country, or any of them acting in their sovereign capacity, acts of Client's contractors or Agents, fires, floods, epidemics, riots, quarantine restrictions, strikes, civil insurrections, freight embargoes, and weather, which in AWT's sole judgment, may affect the services.

16.0 Indemnification.

16.1 Client agrees to indemnify and hold harmless AWT against all claims, suits, losses, and liabilities on account of injuries to, or death of persons (including employees of either party), or damage to property, in connection with or as a result of the performance of the Services undertaken pursuant to this Agreement except when such injuries, death, or property damage were the result of the sole negligence of AWT, or intentional act of AWT beyond the scope of the Services.

16.2 Client agrees to indemnify and hold harmless AWT from all claims, suits, losses, and property liability resulting from unusual subsurface conditions and from damage to subsurface structures owned by Client or third parties which occurs in the performance of the Services, whose nature, presence or locations were not revealed to AWT, and to reimburse AWT for expenses in connection with any such claims or suits, including attorney's fees. Unusual subsurface conditions, for the purpose of this paragraph, shall be determined to be subsurface conditions other than those which professional competent consultants using that degree of care and skill ordinarily exercised by and consistent with the standards of competent consultants practicing in the same locality as the project, and relying on information provided by Client or available to the public through literature or record searches, and on its own specialized training and expertise, would reasonably expect to be present.

16.3 Absent negligence for which AWT, its agent or subcontractors is solely responsible, or an intentional act by AWT, its agents or subcontractors beyond the scope of the Services, Client agrees to indemnify, defend and hold harmless AWT against any claims by the owner or persons having possession of the Site other than Client which are related to alteration or damage at the Site due to the performance of the Services.

17.0 Insurance.

AWT shall maintain at its own expense the following insurance subject to normal industry exclusions: (1) Workmen's Compensation Insurance for statutory obligations imposed by Workman's Compensation or occupational disease laws; (2) Employer's General Liability Insurance; (3) Comprehensive Automobile Liability Insurance; (4) Professional Liability Insurance; (5) Pollution Liability Insurance. Certificates can be issued upon request identifying details and limits of coverage. Client agrees that liability on behalf of AWT shall be limited and shall not exceed the contracted value of services as specified in Attachment A.

18.0 Service to be Performed by Others.

AWT has explained to Client that in AWT's professional opinion, the following services may be essential for the successful fulfillment of Client's project objectives. Client has informed AWT of Client's intent to have the services in question performed by another competent party: construction, construction inspection, laboratory testing, land surveying, architectural design or consultation.

19.0 Delegation And Assignment.

AWT may delegate, orally or in writing, the performance of the Services to be provided by AWT under this agreement. Any such delegation shall not relieve AWT of its responsibilities under this Agreement.

20.0 Attorneys' Fees.

In the event of any action brought by either party against the other arising out of this Agreement, or for the purposes of enforcing the Agreement or collection of any damages alleged to have resulted to one of the parties by reason of the breach or failure of performance of the other, the party prevailing in any such action shall be entitled to recover reasonable attorneys' fees and cost of suit as may be determined by the court.

21.0 Entire Agreement.

21.1 This Agreement, including all attachments and amendments to this Agreement, all proposals for services to be rendered by AWT, and other documents incorporated into the above by reference, represents the entire understanding and agreement between the parties hereto related to the Services and supersedes any and all prior agreements, whether written or oral, that may exist between the parties regarding same.

21.2 To the extent that any additional or different Terms or Conditions of this Agreement, the Terms and Conditions of this Agreement shall govern. No amendment or modifications to this Agreement or any waiver of any provisions hereof shall be effective unless in writing, signed by both parties.

22.0 Modification of Agreement.

This Agreement may not be modified except in writing signed by the parties hereto.

23.0 Notice.

All notices required to be given hereunder shall be in writing and shall be deemed to be delivered if personally delivered or dispatched by certified or registered mail, return receipt requested, postage paid, addressed to the parties as follows:

Client:

Dawn Regan

5534 E. Granger Street

Inverness, Florida 34452

dawnereg@gmail.com

AWT:

Agri-Waste Technology, Inc.

Attn: Jeff Vaughan

501 N. Salem Street, Suite 203

Apex, NC 27502

Notice shall be deemed given on the date that it is deposited in the mail in accordance with the foregoing. Any party may change the address to which to send notices by notifying the other party of such change of address in writing in accordance with the foregoing.

24.0 Paragraph Headings.

The subject headings of the paragraphs of this Agreement are included for purposes of convenience only and shall not affect the construction of interpretation of any of its provisions.

25.0 Severability.

In the event that any of the terms of this Agreement are held to be partially or wholly invalid or unenforceable for any reason whatsoever, such holdings shall not affect, alter, modify or impair in any manner whatsoever, any of the other terms, or the remaining portion of any term, held to be partially invalid or unenforceable.

26.0 Gender.

Whenever required by the context, the singular number shall include the plural number, the plural number shall include the singular number, the masculine gender shall include the neuter and feminine genders and vice versa.

27.0 Waiver.

The failure of AWT or Client at any time to demand strict performance by the other of any terms, covenants or conditions set forth herein shall not be construed as a continuing waiver or relinquishment thereof, and either party may, at any time, demand strict and complete performance by the other of said terms, covenants or conditions.

28.0 Governing Law/Venue.

It is the intent of the parties hereto that all questions with respect to the construction of this Agreement and the rights and liabilities of the parties hereto shall be determined in accordance with the provisions of the laws of the state of North Carolina, in such case made and provided. Venue, for the purposes of this Agreement, shall be considered the county of Wake and state of North Carolina.

29.0 Invalid Provision.

The invalidity or unenforceability of any other particular provision of this Agreement shall not affect the other provisions hereof, and this Agreement shall be construed in all respects as if such invalid or unenforceable provisions were omitted.

30.0 Counterparts.

This Agreement may be executed in two (2) or more counterparts, each of which shall be deemed an original but all of which together shall constitute one and the same instrument.

ATTACHMENT A

SCOPE OF SERVICES

This attachment outlines the specific tasks to be performed by Agri-Waste Technology, Inc. during the term and under the conditions specified in that certain Agreement for Professional Services with **Dawn Regan, 05/02/2022**.

A. Services Provided:

In-field inspection service & summary report that serves the property at the address agreed upon by the client & AWT in its online scheduling system.

Budget Estimate:

Dawn Regan will be billed as follows in order to complete the work described in A, above:

Well Inspection/Lab Analysis (ONLY):

- \$275.00 (Coliform bacterial analysis)

- **\$325.00—FHA/VA/HUD (Coliform bacterial analysis, Lead, Nitrate/Nitrite)**
- **\$450.00—Level 1 (Everything in FHA/VA/HUD – PLUS: Antimony, Arsenic, Barium, Beryllium, Cadmium, Calcium, Chromium, Copper, Iron, Magnesium, Manganese, Mercury, Nickel, Selenium, Silver, Sodium, Thallium, Uranium, Vanadium, Zinc, Hardness)**
- **Other/Additional parameters to be invoiced at agreed upon rate between Client & AWT.**

Well Inspection/Lab Analysis DURING THE SAME VISIT with a Septic Inspection (price added onto septic inspection cost below):

- **\$55.00 (Coliform bacterial analysis)**
- **\$118.00—FHA/VA/HUD (Coliform bacterial analysis, Lead, Nitrate/Nitrite)**
- **\$250.00—Level 1 (Everything in FHA/VA/HUD – PLUS: Antimony, Arsenic, Barium, Beryllium, Cadmium, Calcium, Chromium, Copper, Iron, Magnesium, Manganese, Mercury, Nickel, Selenium, Silver, Sodium, Thallium, Uranium, Vanadium, Zinc, Hardness)**
- **Other/Additional parameters to be invoiced at agreed upon rate between Client & AWT.**

Septic Inspections (Included Systems: Gravity, Pump, Pressure Manifold, Low-Pressure-Pipe):

- **\$300.00 – No hand excavation required**
- **\$350.00 – Hand excavation required to access one of the tank lids**
- **\$375.00 – Hand excavation required to access multiple tank lids**

Septic Inspections (Pretreatment/Drip/Spray/Other Alternative System Not Included Above):

- **\$400.00 – No hand excavation required**
- **\$450.00 – Hand excavation required to access one of the tank lids**
- **\$475.00 – Hand excavation required to access multiple tank lids**

Transmitter/Detector Device:

- **\$100.00 – If required to locate tank(s)**

Septic Tank Pumping (If performed during inspection by AWT):

- **\$300.00 for one tank (in addition to inspection costs above) – Subcontracted by AWT (if elected by client)**
- **\$350.00 for two tanks (in addition to inspection costs above) – Subcontracted by AWT (if elected by client)**

Re-Inspections, Additional Visits, Multiple Systems on One Property:

- **Leak tests - \$100 plus mileage for each visit, no more than 3 visits will be required**
- **Re-inspections to check on repairs - \$150 plus mileage**
- **Any other additional visits or sites with more than one system will be priced on a case by case basis**

Inspections outside normal service area:

- **Inspections with a distance of a 50-75 mile radius from AWT's office will cost an additional \$75 to cover travel costs. Inspections with a distance of greater than a 75 mile radius from AWT's office will be priced on a case by case basis.**

***Please note: The definition of a complete inspection is complete access to the septic system in accordance with House Bill 688, effective January 1, 2008 and the creation of the North Carolina On-Site Wastewater Contractor/Inspector Certification Board. All AWT inspectors are certified by the Board. AWT septic inspections follow the standards of practice for the NCOWCICB.**

Well/septic system inspections constitute a snapshot evaluation in time of the system(s) and do not guarantee future performance of the system(s) due to numerous factors including; but not necessarily limited to, the following: water use patterns of the inhabitants of the dwelling, occupancy of the dwelling (no occupancy for an extended period of time or occupancy in excess of the system design parameters), acts of God or natural disasters, lack of visibility of many of the system components, placement of inappropriate items into the system (non-degradable items, water softener brine, etc.), physical disturbance of or damage to the system or system components, etc.

AWT may not be able to excavate certain components of a septic system if obstructions such as trees, bushes, landscaping, gravel, patios, decks, walkways, pavement, etc. are present. Additionally, an excavator machine may be needed when a septic tank depth is greater than about 30" or more. These issues will be presented to the client when appropriate to discuss scheduling, pricing, timelines, etc.

We will make every effort to obtain the records (permit, design specifications, drawing, etc.) for the septic system from the local county health department or other appropriate permitting agency, but we cannot guarantee that the records will be provided to us or that the records provided to us are accurate.

**ATTACHMENT 3: Industry Standard Septic System
Maintenance Information – Authored by
North Carolina State University
Personnel, North Carolina Cooperative
Extension Service Personnel, and Wake
County Department of Environmental
Services Personnel.**

**No endorsement from the North Carolina Onsite Wastewater Contractors &
Inspectors Certification Board**

HOMEOWNER GUIDE FOR UTILIZATION AND MAINTENANCE OF ON-SITE WASTEWATER DISPOSAL SYSTEMS

What is an On-site Wastewater Disposal System?

There are a number of different types of on-site wastewater disposal systems each designed for a specific set of site conditions. However, there are several system components that are common to most systems. These include the following:

1. A septic tank - a concrete tank that is designed to receive wastewater from the house and to provide a degree of pretreatment for the waste, chiefly through removal of some of the solids in the waste. Note that these solids accumulate over time and necessitate periodic pumping of the septic tank. Currently septic tanks are equipped with two access risers (normally constructed of concrete) which are designed to be at least 6 inches above the ground surface to prevent surface and shallow groundwater from entering the septic tank and to provide access for maintenance. **Care must be taken not to damage or cover these risers so that water inflow / infiltration can be prevented and the tank can be accessed for maintenance.**
2. In some installations, a pump tank - a concrete tank, very similar to the septic tank, which contains a pump along with the associated controls / componentry. The pump tank and pump is designed to receive effluent from the septic tank, and pump the effluent to a disposal field located at a higher elevation and/or to a pressurized distribution network in the disposal field. **The pump tank also has an access riser which must be protected in a similar manner to that indicated for the septic tank.** Servicing of the pump tank components often necessitates the assistance of a professional such as a septic tank installer or Certified Subsurface System Operator. The latter is required for operation and maintenance of certain types of systems.
3. A disposal field - a series of subsurface trenches and lines that are designed to distribute the effluent into the soil and provide for the ultimate treatment and disposal of the effluent. There are numerous variations on the design of the disposal field, related chiefly to the type of system chosen, site constraints, etc. Dependent on the type of disposal system, you may have to maintain a contract with a Certified Subsurface System Operator for operation and maintenance of your wastewater disposal system.

Utilization of Your Wastewater Disposal System

In order to obtain the maximum efficiency and life expectancy from your system, the following simple procedures must be adhered to:

1. **Practice water conservation.** This can include many practical considerations such as not leaving the water running while you brush your teeth, not overfilling the tub, limiting time in the shower, not replacing low flow fixtures with those of higher flows, over rinsing dishes (allow the dishwasher to do its job), immediate repair of any leaking fixtures, running washing machines and dishwashers only when full, etc.

NOTE: Washing machines generate significant volumes of wastewater. As a result, laundry activities should be spread over the week as opposed to accumulating all of laundry until the weekend.

2. **Do not utilize your wastewater disposal system as a trash can by dumping nondegradables down your drains or toilet.** These include cigarette butts, sanitary products, grease, plastics, disposable diapers, etc. Avoid use of garbage disposals. Do not retrofit garbage disposals unless the system is specifically permitted for their use. Also, do not dump harmful chemicals down the drain. These include petroleum products, paint, paint thinner, pesticides, antifreeze, etc.

Maintenance of Your Wastewater Disposal System

Every wastewater disposal system requires maintenance in order to function properly. The specific maintenance required is related to the type of system. The following are general considerations that apply to all systems.

1. **Protect your wastewater disposal system components including the tanks, access risers, disposal field and associated components.** Do not drive or park on any portion of the system. The area over the disposal field should be left undisturbed with the grass cover being maintained as you would your lawn. Location of trees and shrubs on or in close proximity to the disposal field is not recommended since roots may clog or damage your drain lines. Additionally, great care must be exercised when considering the addition of any structure(s) to the site. The location of any appurtenances cannot encroach on the installation or repair areas for your system. It is not recommended that irrigation systems be located in proximity to the disposal system since their construction can cause system damage and/or result in additional hydraulic load on the disposal field.
2. **Protect the system from excess surface and shallow groundwater.** The land surface on and around the wastewater disposal system should be landscaped to shed rainfall and runoff and prevent ponding. Be sure that foundation drains, runoff from roofs and drives, etc. are diverted away from the disposal system.
3. **Regularly have the septic tank / pump tank pumped and cleaned by a permitted septage hauler.** Although the necessary frequency of pumping varies with the household and system, most tanks need **pumping at a frequency of 3-5 years** and at any time solids occupy one-fourth to one-third of the septic tank liquid depth.

Note that all septic tanks being currently installed incorporate an effluent filter within the outlet compartment of the septic tank. This filter is to be cleaned anytime the septic tank is pumped. If plumbing becomes sluggish, this filter should be checked. If filter service is found to be necessary, the tank is to be pumped, the filter cleaned and the filter reinstalled.

4. **Be alert to warning signs that your system may not be functioning properly.**
These include sewage surfacing over the disposal system, sewage backups / slow draining in the house, lush growth over the disposal system, sewage odors, etc.
5. **Do not make or allow repairs to your system unless all necessary permits are obtained from Wake County Department of Environmental Services.**
6. **Commercial additives for septic tank systems** - It has generally not been demonstrated that these additives enhance the function of septic systems or reduce the need for tank pumping and other necessary maintenance.
7. **Special maintenance considerations** - As already alluded to, some of the more complex wastewater disposal systems require that you retain / maintain the services of a Certified Wastewater System Operator in order to comply with Laws and Rules and maintain a valid operation permit for your system. In Wake County this maintenance requirement should be recorded with Register of Deeds if applicable.

Where Do I Obtain Information and Assistance?

If you are purchasing a new home, you should request a copy of your wastewater system permit from the builder / seller along with information regarding any special maintenance requirements. You may also obtain information and assistance from the **Wake County Department of Environmental Services**, 336 Fayetteville Street Mall, Raleigh, NC, Telephone (919) 856-7400. The County also maintains an Internet web site at <http://www.wakegov.com/directory/wwds>. This site contains much useful information and a number of links.

WEL 3/15/04



Soil Facts

Septic Systems and Their Maintenance

The septic tank, soil-treatment system (also called a septic system) is an effective, long-standing method for collecting, treating, and disposing of sewage from rural and suburban homes and businesses. Septic systems are used in every county in North Carolina. Nearly 50 percent of the state's homes have them, and new systems are being installed at a rate of more than 40,000 per year. This fact sheet will answer some typical questions about septic systems and their maintenance.

Why Use a Septic System?

Septic systems are used when centralized sewage treatment plants are not accessible in a community. They safely treat and dispose of wastewaters produced in the bathroom, kitchen, and laundry. These wastewaters may contain disease-causing germs and pollutants that must be treated to protect human health and the environment. Septic systems are usually a permanent solution to wastewater treatment and disposal. Therefore, they must be properly used, operated, and maintained by the homeowner to assure the long-term performance of these systems. Even when used as a temporary wastewater treatment solution until sewer lines are extended to a community, special care and maintenance are needed for septic systems so that they don't pose a risk to public health or the environment.

What Is a Septic System?

Several different types of septic systems are available, each with its own design. The traditional, conventional system is the one that has been most commonly used in North Carolina up until the past decade (Figure 1). *It consists of three main parts: the septic tank, the drainfield, and the soil beneath the drainfield.*

The septic tank is a watertight container about 9 feet long and 5 feet tall. It is buried in the ground just outside the home. The tank is usually precast from reinforced concrete, although tanks made from plastic or fiberglass may be seen on occasion. While a tank is typically designed with a 1,000-gallon liquid capacity, its size is legally determined by the number of bedrooms in the home. The tank temporarily holds household wastes and allows a small amount of pretreatment to take place (Figure 2).

What Takes Place in the Septic Tank?

All of the wastewaters from the home should flow into the septic tank. Even waters from the shower, bathtub, and washing machine can contain disease-causing germs or environmen-




Figure 1. A conventional septic system.

Distributed in furtherance of the Acts of Congress of May 8 and June 30, 1914. North Carolina State University and North Carolina A&T State University commit themselves to positive action to secure equal opportunity regardless of race, color, creed, national origin, religion, sex, age, or disability. In addition, the two Universities welcome all persons without regard to sexual orientation. North Carolina State University, North Carolina A&T State University, U.S. Department of Agriculture, and local governments cooperating.




Figure 2. A two-compartment septic tank.

tal pollutants. As wastewater flows into the tank, the heavier solid materials settle to the bottom (forming a sludge layer), and the lighter greases and fats float to the top (forming a scum layer). The tank's primary purpose is to retain the solids. After a retention time of about two days, the liquid portion (the sewage effluent) flows out of the tank through the outlet pipe. The retention time is necessary for separation of the solids from the liquid and for anaerobic digestion of the solids to begin in the septic tank.

An outlet baffle (or a sanitary tee at the outlet end) prevents solids from flowing out with the liquids. Newer septic systems installed since 1999, however, include an effluent filter in the septic tank. These are installed in place of the sanitary tee at the outlet end of the septic tank (in the second compartment shown in Figure 2).

What Happens in the Drainfield and the Soil?

The purpose of the drainfield is to deliver the liquid sewage effluent to the soil. The real treatment of the wastewater occurs in the soil beneath the drainfield. Sewage effluent flows out of the tank as a cloudy liquid that still contains many disease-causing germs and environmental pollutants. Effluent flows into the perforated pipe in the trenches, passes through the holes in the pipe, and then trickles

down through the gravel to the soil (Figure 3). There are also "gravel-less" trenches used where plastic louvered chambers, polystyrene aggregate, tire chip aggregate, large diameter pipes, or multiple small pipes are used in place of the gravel aggregate. These materials provide a void space in the trench to allow distribution of the effluent to the trench bottom. As sewage effluent enters and flows through the ground, soil particles filter out many of the bacteria that can cause diseases. The soil

adsorbs some of the smaller germs, such as viruses, until they are destroyed. The soil can also retain certain chemicals, including phosphorus and some forms of nitrogen.

A special zone, called a biomat, forms in the upper 1 to 6 inches of the soil at the soil/trench interface just below the trench bottom. This biomat zone is useful. It helps remove many of the germs and chemical pollutants. If the solids accumulating in the septic tank are never pumped out, however, they can flow into the trenches and accumulate into an intensive biomat that becomes too thick. When that happens, the biomat completely clogs the soil and does not allow the sewage effluent to flow out of the trench. An improperly maintained system will fail and cause untreated sewage to completely fill the trenches and come out on top of the ground or back up into the home in its plumbing system.

Where Can a Septic System Be Used?

A centralized sewer system with a large sewage treatment plant usually




Figure 3. Wastewater treatment and disposal in the soil.

discharges treated wastewater into a body of water. On the other hand, a septic system depends on the soil around the home to treat and dispose of sewage effluent (Figure 3). For this reason, a septic system can be used only on soils that will adequately absorb and purify the effluent. If a septic system is installed in soil that cannot do so, the effluent will seep out onto the soil surface overlying the drainfield or back up into the home. In addition to causing an unpleasant smell, this untreated sewage can pose health problems.

In some cases where the soils do not adequately absorb the wastewater, the toilets and sinks might not drain freely. If the soil can absorb the effluent, but not treat it, or if the trenches are installed directly into groundwater or bedrock, the sewage may contaminate the groundwater. Because the underlying groundwater serves as the source of drinking water for your well or possibly your neighbors' wells (Figure 3), it is very important that the system be installed in the proper soil conditions and that the septic system is correctly used, operated, and maintained.

What Kinds of Soil Conditions Are Best Suited To a Conventional Septic System?

Gently sloping, thick, permeable soils with deep water tables make the best sites for the traditional, conventional septic system and simple modifications of it. The soil should be a uniform brown, yellow, or bright red color. It should not have spots of gray colors that often indicate the soil becomes excessively wet or that groundwater comes up close to the ground surface during the wet times of the year. The soil texture should be neither too sandy nor too clayey, and it should have good aggregation, or structure (that is, a handful of the soil should easily break apart into small aggregates).

Areas that are unsuitable for conventional septic systems have rock close to the surface, very sticky clays, soil

layers that restrict the downward flow of water, or areas with shallow groundwater. These factors would prevent a conventional septic system from working properly.

What About Other Types of On-Site Systems That Are Alternatives to the Conventional System?

Other types of on-site systems are sometimes used on sites where the soil is not suited to a conventional system. Where soils are too wet or too shallow for the conventional system, the drainfield might be placed very close to the ground surface in the upper layers of the soil. In some wet soils, artificial drainage around the septic system lowers the level of the shallow water table. On some clayey soils that have a thick sandy surface, the low-pressure pipe (LPP) system provides an alternative.

On some soils that are not deep enough to provide adequate treatment of the sewage effluent, it may be possible to use an advanced pretreatment unit to supplement the soil's treatment capacity. Examples are fixed media biofilters such as a sand filter, peat filter, textile filter, or porous foam biofilter or mechanical aerobic treatment units that bubble air into the sewage itself. Most of these pretreatment units are installed between the septic tank and drainfield. They provide better purification of the wastewater than is provided by the traditional septic tank alone. Some sites may need more sophisticated methods of distributing the sewage effluent within the drainfield itself using a pressure manifold, LPP, or drip irrigation system. These systems use pumps, special controls, and specially designed pipe networks that can improve the wastewater treatment in the soil. In other situations, it may be cost effective to collect the wastewater from several homes in an area or subdivision by using a cluster system. This type of system has a drainfield located in a common area within the best-suited soils in the tract

of land. These newer and more sophisticated types of on-site system options can often provide a better wastewater treatment solution for a particular building lot, or a tract of land, than either the traditional, conventional septic tank system or large-scale, centralized public sewers.

How Do I Know if My Site is Suitable for a Septic System?

North Carolina has more than 400 different kinds of soil, and a 1-acre lot can contain several different soil types. Because many of these soils are unsuitable for conventional septic systems and even unsuitable for more advanced or alternative on-site systems, you should always obtain an improvement permit (I.P.) before purchasing a lot that you intend to build on. You will submit an application and a site plan to the county health department. The environmental health specialist (sanitarian) will conduct a comprehensive soil and site evaluation and either issue or deny the permit. If an I.P. can be issued, you will also need to obtain a construction authorization (C.A.) before a building permit can be issued.

If you are interested in developing a tract of land to subdivide, you should hire a licensed soil scientist to conduct preliminary evaluations and advise you on the location of suitable soils and lot configuration. You can obtain additional information from the Cooperative Extension publication (AG-439-12), *Investigate Before You Invest*, available online at www.soil.ncsu.edu/publications/Soilfacts/AG-439-12/.

How Large is a Typical Drainfield?

Usually, the drainfield for a home can fit within the front yard or the backyard of a typical 1-acre home site. Sometimes smaller lots can be used. The precise area requirements will depend upon the kinds of soils at the home site, the size of the house (the number of bedrooms), the topography of the lot, and the type of on-site

system used there. A site with clayey, slowly permeable soils needs a larger drainfield to absorb the sewage effluent than does a site with sandy, permeable soils. A home with five bedrooms will need a larger tank and drainfield area than a home with three bedrooms. A rental property at the beach may require a larger drainfield than a similar-sized permanent residence with the same number of bedrooms. A home using one of the newer, more advanced types of on-site technologies may be able to use a smaller area for the drainfield than if a conventional septic system is installed. Adequate land area must be available to achieve adequate setback distances from any nearby wells, springs, streams, lakes, or other bodies of water located either on the lot or off-site.

There also must be enough area to install a second system, called a replacement system, in case it is ever needed. This replacement area (sometimes called a repair area) also must have acceptable soil and site conditions and must be left undisturbed and available for system replacement. Be aware that the type of on-site system required for use in the repair area could be a completely different, more sophisticated type of on-site system. Hence, if that repair area is ever needed, you might have to install a more expensive system than the original system installed when the lot was first developed.

What Legal Requirements Regulate Septic Systems?

State law requires that soils be evaluated by the local health department and that an I.P. and a C.A. be issued before house construction begins or the septic system is installed. The I.P. allows the site to be used, while the C.A. determines what type of system must be installed. Sometimes these are issued at the same time by the health department. An I.P. is good only for five years unless it is renewed, or unless it is issued under special conditions for a lot that has been professionally surveyed. If a permanent I.P. is issued,

then you have some limited guarantee that the lot can be used (even if the state rules change), assuming that the conditions on the lot or the intended use don't change. Nevertheless, the type of system that will be required as well as home size and location are not assured until the C.A. is issued. Contact your local health department to be sure that you follow the correct procedures and that you are fully aware of the limitations that will protect your investment. Also, the installation must be approved by the health department and an operation permit (O.P.) must be issued by the health department before electrical service can be permanently connected to the home and the septic system put into use.

Once the home has been occupied and the system put into use, you will need to contact the county health department if you plan to add on to the home, install a pool, build an outbuilding, or engage in activity that requires a building permit. First, obtain an authorization from the county health department to make sure that the septic system and repair area remain intact and are properly sized for the proposal.

What Maintenance Is Needed?

Both the septic tank and the drainfield must be properly maintained for the standard conventional septic system. With conscientious maintenance, the system should work correctly for many years. Such maintenance begins with water use and waste disposal habits. Your family will determine which materials enter the system, so you should establish family rules for proper use and maintenance. The suggestions outlined in the box will save you anguish and money when applied to most conventional systems.

If your system has an effluent filter, it will need checking and servicing approximately every 2 to 3 years. While this could be done by a homeowner, it is a messy, unpleasant task and there are potential safety issues because of the germs in the sewage and toxic gases. For most people, it would be appropriate to hire a company that specializes in septic system maintenance and service to inspect and clean the effluent filter.

Special types of pretreatment units and drainfield distribution technologies also must be carefully maintained for the more advanced, newer tech-

Tips for Maintaining Your Septic System

- Do not put too much water into the septic system; typical water use is about 50 gallons per day for each person in the family.
- Do not add materials (chemicals, sanitary napkins, applicators, and so on) other than domestic wastewater.
- Restrict the use of your garbage disposal.
- Do not pour grease or cooking oils down the sink drain.
- Make a diagram showing the location of your tank, drainfield, and repair area.
- Install a watertight riser over the septic tank to simplify access.
- Have the effluent filter in the septic tank cleaned periodically by a professional.
- Have the solids pumped out of the septic tank periodically.
- Maintain adequate vegetative cover over the drainfield.
- Keep surface waters away from the tank and drainfield.
- Keep automobiles and heavy equipment off the system.
- Do not plan any building additions, pools, driveways, or other construction work near the septic system or the repair area.

nologies described earlier. These newer technologies will be more expensive to operate and maintain than the traditional, conventional septic system. Most advanced on-site and cluster wastewater treatment systems require regular inspections and professional maintenance. Research conducted in North Carolina has shown that about 40 to 50 percent of the advanced systems will fail within 6 years if this maintenance is not provided. Therefore, in North Carolina, a professionally trained, state-certified “subsurface system operator” hired by the homeowner is required by the O.P. to provide the needed inspections and maintenance for advanced technologies. For more information about these requirements, contact your local health department or the state Water Pollution Control Systems Operator Certification Commission.

Note, however, that individual homeowners are allowed to take the same training programs and state licensing exam as the professional operators. If they pass the exam, they can operate their own system by themselves. Because this generally is not done, most homeowners will have to pay for this service if they have one of these more advanced technologies.

Regardless of whether a professional operator is hired, it is the homeowner’s responsibility to assure proper use, inspection, operation, and maintenance of any type of on-site wastewater system.

Will I Need to Pump the Tank?

Yes. After a few years, the solids that accumulate in the septic tank should be pumped out and disposed of at an approved location. If not removed, these solids will eventually overflow, accumulate in the drainfield, and clog the pores (openings) in the soil.

This blockage severely damages the drainfield. Although some clogging of soil pores slowly occurs even in a properly functioning system (the biomat described earlier), excess

solids from a poorly maintained tank can completely close all soil pores so that no wastewater can flow into the soil. The sewage effluent will then either back up into the house or flow across the ground surface over the drainfield. If this happens, you may need to construct a new drainfield on a different part of your lot. Pumping the septic tank after the soil drainfield has become completely clogged will not rejuvenate the system. It will provide only a few days of reprieve until the tank fills up again. Once the soil has become completely clogged, it is usually necessary to install a new drainfield or an advanced pretreatment unit, or both. This can have a significant negative effect on your landscaping and yard, as well as being expensive. An ounce of prevention is worth a pound of cure with septic systems.

How Will I Know When to Pump the Tank?

The frequency with which you will need to pump depends on three variables: the tank size, the amount of water used by your family, and the solids content of your wastewater. If you are unsure about when to have the tank pumped, have a professional operator observe the rate of solids accumulation in the tank each year. He or she can clean and replace the effluent filter cartridge in the tank at the same time. The tank should be pumped if the sludge layer at the bottom of the septic tank has built up to within 25 to 33 percent of the

tank’s liquid capacity or if the scum layer in the tank is more than 4 to 6 inches thick. Therefore, a typical 1,000-gallon tank with a 4-foot liquid capacity should be pumped when the solids reach 1-foot thick in the tank bottom. If the tank is not easily accessible and the rate of solids accumulation cannot be checked yearly, then you may wish to inspect and pump it according to the frequency guidelines in Table 1. Your local health department should be able to tell you the size of your tank. When inspecting the tank, check the effluent filter (or for older systems check the sanitary tee or the outlet baffle to be sure that it has not broken off and dropped into the tank). **Also, be sure to have both compartments of the tank pumped (note the two compartments shown earlier in Figure 2).**

If the septic system is not used very often (as in an infrequently used vacation home with a correctly sized tank), it will probably not need to be pumped as frequently as indicated in Table 1. If you use a garbage disposal, the tank may need to be pumped more frequently. After a few inspections, you should be able to adjust the schedule according to the rate at which solids accumulate.

What Should Not Be Put into the Septic System?

Make sure you are aware of the types and amounts of extra waste materials that are poured down the drain. Limiting the use of your garbage disposal will minimize the flow of excess

Table 1. Estimated Septic Tank Inspection and Pumping Frequency (in Years)					
Tank Size (gallons)	Number of People Using the System				
	1	2	4	6	8
900	11	5	2	1	<1
1,000	12	6	3	2	1
1,250	16	8	3	2	1
1,500	19	9	4	3	2
Source: Adapted from “Estimated Septic Tank Pumping Frequency,” by Karen Mancl, 1984, <i>Journal of Environmental Engineering</i> . Vol. 110(1):283-285.					

solids to your tank. Garbage disposals usually double the amount of solids added to the tank.

Do not pour cooking greases, oils, and fats down the drain. Grease hardens in the septic tank and accumulates until it clogs the inlet or outlet. Grease poured down the drain with hot water may flow through the septic tank, but then it can clog soil pores completely and ruin the drainfield.

Pesticides, paints, paint thinners, solvents, disinfectants, poisons, and other household chemicals should not be dumped down the drain into a septic system because they may kill beneficial bacteria in the septic tank and soil microorganisms that help purify the sewage. Also, some organic chemicals will flow untreated through the septic tank and the soil, thus contaminating the underlying groundwater.

If your home has a water treatment system, such as a water softener, the discharge pipe from the backwash should not be connected to the waste plumbing system or septic tank.

Are Septic-Tank Additives Necessary?

No. These products include biologically based materials (bacteria, enzymes, and yeast), inorganic chemicals (acids and bases), or organic chemicals (including solvents). Research conducted to date on three of these types of bacterial additives has not shown any reduction in the rate of solids buildup nor increases in bacterial activity in the septic tank. Therefore, they do not seem to reduce the need for regular pumping of the septic tank. Some additive products contain organic chemicals and may even damage the drainfield or con-

taminate the groundwater and nearby wells.

Is Special Care Needed for the Drainfield?

Yes. The drainfield does not have an unlimited capacity. The more water your family uses, the greater the likelihood of problems with the septic system.

Water conservation practices can help reduce the amount of wastewater generated in the home. Periodically check your plumbing for leaky faucets and toilets. Uncorrected leaks can more than double the amount of water you use. Many soils can absorb the 200 to 250 gallons of sewage usually produced each day by a family of four, but these soils would become waterlogged if an extra 250 gallons were added. For more information on this subject, see North Carolina Cooperative Extension Service publications WQWM-75/HE-250, *Focus on Residential Water Conservation* and WQWM-76/HE-213, *Water Management Checklist for the Home*. These publications can be viewed and printed online at www.bae.ncsu.edu/programs/extension/publicat/wqwm/usewtr.html.

Be sure that foundation drains, roof waters, gutter waters, and surface waters from driveways and other paved areas do not flow over the septic tank or the drainfield. Careful landscaping can help direct excess surface waters away from the system.

Summary

The septic system is an efficient, inexpensive, and convenient method for treating and disposing of household wastewater. Because not all soils are suited for conventional systems,

comprehensive soil and site investigations must be performed before you purchase any land.

Septic systems will adequately absorb and purify wastewater if they are properly maintained.

Contrary to popular belief, septic systems are not maintenance free. Money that is saved by not paying a monthly sewer bill should be set aside for regular inspections and maintenance. A few precautions can save you anguish and money. Reducing water use, avoiding grease, cleaning the effluent filter, pumping the tank periodically, and properly landscaping the yard to keep surface water away from the tank and drainfield are inexpensive precautions that can help assure your system a long life. The North Carolina Cooperative Extension publication AG-439-22, *Septic System Owner's Guide*, summarizes some important day-to-day management and periodic maintenance activities to improve your system's longevity. When properly located and maintained, your system should provide years of trouble-free, low-cost service.

Reference

Mancl, K.M. 1984. *Journal of Environmental Engineering*, Vol. 110(1):283-285.

Prepared by

Michael T. Hoover, Extension Soil Science Specialist, Department of Soil Science, North Carolina State University

Tom Konsler, Environmental Health Supervisor, Orange County Health Department


Appreciation is extended to Mitch Woodward, Grace Lawrence, and Deanna Osmond for their assistance in review of this publication and to Janet Young for graphic design, layout, and editing.

20,000 copies of this public document were printed at a cost of \$2,767 or \$0.14 each.

© 2004 North Carolina State University

Published by

NORTH CAROLINA COOPERATIVE EXTENSION



Soil Facts

Septic System Owner's Guide

If you use a septic system, or if you are buying a home with a septic system, this owner's guide can help you be sure that your septic system is used and maintained properly. This folder also provides a place to record and keep important information, such as a copy of your permit, a sketch of your system, maintenance records, and other fact sheets.

Know the Ins and Outs of Your System

What type of system do you have?

Many different kinds of septic systems are used in North Carolina, but most of the nearly 2 million systems in use throughout the state are slight modifications of the conventional septic system. This system has a septic tank and a drainfield with gravel-filled trenches (usually two to six trenches). Since the mid to late 1990s, however, the traditional gravel aggregate trenches used in the past have given way to newer gravel-less trench designs.

These gravel-less trench designs rely on alternative materials in place of the gravel. The most common gravel-less trenches now used include either long, narrow, tunnel-shaped chambers in the trenches or gravel substitutes such as expanded polystyrene aggregate.

Other alternative trench materials that are also being used extensively in some parts of the state include large diameter pipes and permeable concrete panel block trench materials. In addition, since about 2003, some gravel-less septic system trenches use bundles of plastic pipes or other materials such as recycled rubber tires (chopped into

chips or pieces to meet specific size requirements) to replace the gravel aggregate.

Cooperative Extension Service publication *AG-439-13, Septic Systems and Their Maintenance*, describes the conventional system, simple modifications of it, and important maintenance needs.

Other more sophisticated types of on-site systems used for the last 20 to 25 years include systems with pumps, mechanical pretreatment units, or biofilters. These technologies are now being used in numerous new housing developments or to replace or repair failing septic systems at homes and businesses. Systems using these new technologies require a higher level of maintenance than the more traditional conventional septic systems.

For this reason, state rules have specific maintenance requirements for a number of these more sophisticated technologies. Often, homeowners will be required by state sewage rules to hire a state-certified operator to regularly inspect and maintain the system. In addition, state rules also require the health department to inspect these systems on a periodic basis.

Your local health department can tell you what type of system you have and what the

Distributed in furtherance of the Acts of Congress of May 8 and June 30, 1914. North Carolina State University and North Carolina A&T State University commit themselves to positive action to secure equal opportunity regardless of race, color, creed, national origin, religion, sex, age, or disability. In addition, the two Universities welcome all persons without regard to sexual orientation. North Carolina State University, North Carolina A&T State University, U.S. Department of Agriculture, and local governments cooperating.

- What type of septic system do you have?
- Where is it located?
- Where is the repair area located?
- Is the septic system working?
- Has it been maintained in the past?
- What can you do on a day-to-day basis to keep your system working properly?
- What maintenance is needed in the future?

To properly maintain your septic system, you should know the location of both the septic tank (and any other pretreatment units) and the drainfield. Contact the local health department for a copy of your septic system permit and soil evaluation sheet. These forms indicate the approximate locations of each of the system's components and the size of the septic tank. Keep these items in this *Septic System Owner's Guide* file folder.

The location of the septic tank and drainfield can usually be determined with a copy of the permit and with the help of a septic contractor, consultant, or the local health department.

Most housing sites permitted since the early 1980s are legally required to have a “repair area or replacement area” in which a second drainfield could be built if needed. This repair area was identified by the health department when the site was permitted and should be shown on your septic system permit. The law also requires you to protect this area from excavation; building a house addition, garage or outbuilding over it; swim-

ming pool construction; and any soil disturbance activities.

Sketch your home, septic system (both the tank and drainfield), repair area, and other important features (such as your driveway) on the grid labeled **Septic System Layout**. When you have your septic tank pumped, measure and record the distance from the house to the access port on the tank. This will help you find it again. You might also wish to mark your tank location and the drainfield boundaries in your yard. If a riser is not installed over the access port for your septic tank, you may want to have one installed. Be sure, though, that the riser is secured with a lock or a heavy lid to prevent children from opening it and endangering themselves or others. Even properly operating septic tanks contain poisonous gases and pollutants as well as bacteria and other germs that can cause serious diseases. **NO ONE SHOULD EVER ENTER A SEPTIC TANK.**

Is your septic system working properly?

Unfortunately, if house fixtures drain well, few people investigate whether their septic system works. Many people don't realize that untreated sewage on top of the ground can be a health hazard. If your system shows signs of problems, contact your local health department immediately.

State law requires that you get a permit from the health department before repairing a failing septic system. Be wary of any contractor who wants to attempt a repair without a permit.

What maintenance has been done?

Before planning a maintenance program, find out what maintenance has already been done. If you are buying an existing home, ask the seller a few important questions:

- How old is the system?

[illegible]

- Where are the tank and drainfield located (they may not be at the same location or even on the same lot)?
- When was the tank last pumped?
- How frequently has it been pumped?
- How often has the “effluent filter” in the septic tank been cleaned (these effluent filters are required on systems installed since 1999).
- Have there been signs of possible failure?
- Where is a copy of the permit and records showing how well (or poorly) the system has been maintained?
- Have there been additions made to the house that would necessitate increasing the size of the system?
- Has the system ever been repaired, and if so, when, and by whom?

If the house has just been built, ask the septic system contractor to provide you an “as built” diagram that may show details not on the permit. If the house has a system with a pump, ask the contractor and health department to provide details concerning the initial pump setup.

Proper care of your septic system requires day-to-day management as well as periodic maintenance and repairs.

Day-to-Day Management

Don't use too much water.

- The drainfield does not have unlimited capacity.
- Typical daily water use is 50 gallons per person.
- The soil drainfield usually has a maximum daily design capacity of 120 gallons per bedroom, even for short periods of time.
- Overloads can occur seasonally, daily, or on the weekend.
- Water conservation will extend the life of your system.
- Repair dripping faucets and toilets.

Limit disposal to sewage.

- Don't use your septic tank as a trash can for cigarette butts, tissues, sanitary napkins, cotton swabs, cat box litter, coffee grounds, or disposable diapers.
- Restrict the use of your garbage disposal. These add quite a lot of extra solids.
- Don't pour grease or cooking oil down the drain.
- Don't poison your system with harmful chemicals such as solvents, oils, paints, thinners, discarded medications, disinfectants, pesticides, poisons, and other substances.
- Save money. Commercial septic tank additives are usually not necessary.

Protect the system from physical damage (site maintenance).

- Keep the soil over the drainfield covered with vegetation to prevent soil erosion.
- Don't drive vehicles over the system.
- Avoid construction over the system and repair area.
- Maintain the natural shape of the land immediately downslope of the system, and protect this area from excavation (cutting and filling).
- Don't cover the tank or drainfield with asphalt or concrete.

Dispose of all wastewater in an approved system.

- Don't put in a separate pipe to carry wash waters to a side ditch or the woods. This is illegal.

Periodic Maintenance and Repair

Home and yard (site maintenance):

- Protect and maintain the site of your septic tank and drainfield.
- Cut down and remove trees that like wet conditions. This includes

willows, elms, sweetgums, and some maples.

- Landscape the yard to divert surface waters away from the tank and drainfield.
- Be sure that the water from the roof, gutters, and foundation drains does not flow over the system.
- If your system is at the base of a slope, then consider installing a french drain to divert underground waters.
- Maintain drainage ditches, subsurface tiles, and drainage outlets so that water can flow freely from them.

Septic tank:

- Install risers over the tank if it is buried 6 inches or deeper. They provide easy access for measuring and pumping solids as well as cleaning the effluent filter.
- Measure how quickly sludge and scum accumulate in the tank. Have your professional pumper record this information.
- Have solids pumped out of the tank as needed. Most septic tanks have two compartments; get both pumped.
- Cooperative Extension Service publication *AG-439-13, Septic Systems and Their Maintenance*, contains more information on pumping frequency.
- Don't wait until your drainfield fails to have your tank pumped. By then, the drainfield may be ruined. With septic systems, an ounce of prevention is worth a ton of cure!

Regulations and precautions:

- Hire a state-certified subsurface system operator for any system with a pump. One will be required by law for low pressure pipe (LPP) systems installed or repaired after July 1, 1992, any subsurface drip irrigation systems, aerobic treatment units (ATUs), peat biofilters, sand biofilters, textile

Preventative Maintenance Record			
Date	Work Done	Firm	Cost

Your Septic System Pumper
Name
Address
Phone

Your Septic System Installer
Name
Address
Phone
Date System Installed

Signs of Possible Septic System Problems

- Sewage backing up into your toilets, tubs, or sinks.
- Slowly draining fixtures, particularly after it has rained.
- The smell of raw sewage accompanied by soggy soil or sewage discharged over the ground or in nearby ditches or woods.
- Note: pump systems sewage may come to the ground surface when the pump is turned on and then disappear after the pump turns off. This is still a system failure and must be repaired.
- An alarm flashing (red light) or beeping in the house or in the yard indicating a pump is not working properly or that the water level in a pump tank is too high and close to failure.
- An increase in infections or illnesses associated with swimming in lakes or rivers next to the system.

biofilters, and other complex systems.

- A list of state-certified subsurface system operators can be obtained from the N.C. Water Pollution Control System Certification Commission at (919) 733-0026.
- Be sure the pump and electrical components continue working properly between scheduled maintenance visits.
- Sewage contains germs that can cause diseases. Never enter a septic tank. Toxic and explosive gases in the tank present a hazard. Old tanks may collapse. Electrical controls present a shock and spark hazard. Secure the septic tank lid so that children cannot open it.
- Don't attempt to repair a failing system yourself. Get a repair permit and hire an experienced contractor.

For more information about septic systems, contact your county Extension agent or local health department.

Prepared by

Michael T. Hoover, *Extension Soil Science Specialist, Department of Soil Science, North Carolina State University*

Appreciation is extended to Tom Konsler (Orange County Health Department), Deanna Osmond, Mitch Woodward, and Grace Lawrence (North Carolina Cooperative Extension) for peer review of the document and to Janet Young for graphic design, layout, and editing.

20,000 copies of this public document were printed at a cost of \$ or \$ each.

© 2004 North Carolina State University

Published by

NORTH CAROLINA COOPERATIVE EXTENSION



Improving Septic Systems

Is your well protected from your septic system?

One of the easiest ways to protect well water from pollution is to check your septic system. Septic systems can pollute wells when they are placed too close to the well, are not properly maintained, or have not been properly installed. The major contaminants from septic systems that enter wells are disease-causing germs. These invisible germs — such as bacteria and viruses — can cause many human diseases. Another potential contaminant that can come from septic systems is nitrogen in the form of nitrate-nitrogen. If the nitrate level of your well water is too high, the water can be hazardous to infants in their first six months of life.

How can we help?

We have prepared this publication to help you focus on potential problems with your drinking water that may be caused by an improperly placed, constructed, or maintained septic system. Read the publication before you begin answering the questions in this publication. Gather any records you have about your septic system: the type of system you have, the location of the septic tank and the drainfield, and the location and type of well on your property. If you do not have records, contact your local health department for a copy of your septic system permit and soil evaluation sheet. Walk around the area near your septic system and look at it closely. Also look at the area around your well.

Each of the following sections deals with different topics. Next to each topic is a question for you to answer. Your answers will help you to see where you have potential problems.

- If you answer a question either a or b, you have few problems with your septic system.
- If you answer a question either c or d, there may be potential problems with the condition of your septic system.
- If you answer a question either c or d, you will want to consider making changes to your septic system in order to protect your drinking water.

If you would like further help in assessing the condition of your septic system, please visit your nearest Cooperative Extension Service Center and talk with your Extension agent.

Employment and program opportunities are offered to all people regardless of race, color, national origin, gender, age, or disability. North Carolina State University, North Carolina A&T State University, U.S. Department of Agriculture, and local governments cooperating.



College of Agriculture & Life Sciences • NC State University
School of Agriculture and Environmental and Allied Sciences •
NC A&T State University

How safe is your drinking water?

If you drink water from a well or spring, the water comes from the ground. Most groundwater in North Carolina is safe to drink. If pollution gets into groundwater, your well or spring water may not be safe. Many things we all do at our homes and farms can pollute the groundwater.

If groundwater becomes polluted, it is nearly impossible to clean up. Then, the only ways to get safe drinking water are to treat the existing water, drill a new well, or get water from another source. All of these options are expensive and inconvenient.

The North Carolina Farm*A*Syst program has a series of publications that can help you keep your drinking water safe. These publications will lead you through an evaluation of your farmstead to determine if your water is in danger of becoming or is already polluted with harmful substances from your farmstead area. If there is a problem or a potential problem, the Farm*A*Syst publications have information about how to solve the problems. The publications also list the North Carolina state agencies that can help you solve your drinking water problem.

The goal of the North Carolina Farm*A*Syst program is to help you protect the groundwater that North Carolina residents depend on for drinking water.

What is a septic system?

A septic system is an efficient, inexpensive, convenient, and safe method for treating and disposing of household wastewater if the system is properly installed and maintained. A septic system consists of three main parts:


1. The **septic tank** collects and stores the solids that come from the house.
2. The **drainfield** is made from pipe and gravel that are installed as trenches in the soil. The drainfield delivers wastewater to the soil.
3. The **soil beneath the drainfield** purifies the wastewater before it flows to the underlying groundwater.

Wastewater flows from the house into the septic tank. The solids sink to the bottom of the tank, the grease floats to the top, and the liquid portion of the wastewater flows out into the drainfield. The drainfield distributes the wastewater and allows it to slowly move into the soil. As it moves through the soil, the wastewater is purified by organisms that live in the soil.

State law requires that soils be evaluated by the local health department and that an improvement permit and an authorization to construct an on-site wastewater system (construction authorization) be issued before house construction begins or the septic system is installed. The purpose of this evaluation is to ensure that the soil can both absorb and treat the wastewater from your home. Septic system

North Carolina Farm*A*Syst Publications

- *Protecting Water Supply*, #1
- *Improving Fuel Storage*, #2
- *Improving Storage and Handling of Hazardous Waste*, #3
- *Improving Septic Systems*, #4
- *Improving Storage and Handling of Pesticides*, #5
- *Improving Storage and Handling of Fertilizer*, #6
- *Improving Storage, Handling, and Disposal of Livestock Waste*, #7
- *Grazing Livestock and Water Quality*, #8
- *Stream Management in the Piedmont and Mountains*, #9
- *Agriculture and Natural Resource Protection*, #10
- *Protecting Your Wetlands*, #11
- *Wildlife on Your Farm*, #12
- *Christmas Tree Production Best Management Practices to Protect Water Quality and the Environment*, #13
- *Managing Pests*, #14



installation must be approved by the local health department before electrical service can be permanently connected to the home, the home occupied, and the septic system put into use.

General Conditions Of Your Septic System

1. How old is your septic system?

North Carolina rules regarding the placement and design of septic systems are being improved over time. Major changes to the state rules occurred in 1977, 1982, and 1992. Current rules require a comprehensive evaluation of the soil before a septic system can be approved for that location. State rules also require homeowners to employ a trained and certified subsurface system operator for certain types of septic systems installed or repaired after 1992. These operators ensure that the system is operating well. The changes in the rules have improved the chances that your septic system will work better.

If you do not know the age and type of your septic system, this information may be available from your local health department.

2. What is the depth between your drainfield and the groundwater table?

Wastewater moves from the septic tank into the drainfield and then slowly into the soil. The drainfield trenches are normally installed 2-3 feet deep. The wastewater is purified as it moves down through the soil and into the groundwater.

North Carolina septic rules require that the groundwater table or soil wetness conditions be at least 12 to 18 inches deeper than the drainfield trenches. Soil above the groundwater table is considered to be *aerobic*. *Aerobic* means that the soil has some air in it and is not totally saturated (or filled with water). This aerobic soil is where most of the germs from the sewage are removed.


Call your local health department or United States Department of Agriculture Natural Resource Conservation Service for information about the soils on your lot.

1. Circle the answer that best describes the age of your septic system.

- a. Your septic system was installed after 1992.
- b. Your septic system was installed between 1982 and 1992.
- c. Your septic system was installed between 1977 and 1982.
- d. Your septic system was installed before 1977; OR do not know.


2. Circle the answer that best describes the relationship between the location of your septic system and the groundwater.

- a. The groundwater always remains at least 4 feet below the surface.
- b. The groundwater normally remains more than 4 feet below the surface except for very short periods of time (less than a week) during wet times of the year.
- c. The groundwater normally remains more than 2 feet below the surface except for very short periods of time (less than a week) during wet times of the year.
- d. The groundwater periodically rises to within 2 feet of the surface; OR do not know.



3. Where are your septic system and well located?

Once the purified wastewater drains through the soil, it becomes part of the groundwater. The best way to protect your drinking water from your septic system is to separate the two. North Carolina law requires that septic systems be placed at least 100 feet away from a well or other water source.



4. What type of soil is your septic system installed in?

The type of soil in which your septic system is located is important for protecting the groundwater from pollution. Gently sloping, deep soils that aren't too clayey or too sandy with a deep groundwater table make the best sites. If the soil is too sandy, wastewater flows through the soil into the groundwater too fast and is not purified. On the other hand, if the soil is too clayey, wastewater flows too slowly, causing untreated sewage to collect on top of the ground. Avoid areas that have rock close to the surface, very sticky clays, or

3. Circle the answer that best describes the relationship between the location of your well and your septic system.

- Your septic system is downhill from your well or other water source and is more than 100 feet away from it.
- Your septic system is uphill from your well or other water source and is more than 100 feet away from it.
- Your septic system is 50 to 100 feet away from your well or other water source.
- Your septic system is less than 50 feet away from the well or other water source; OR do not know.

4. Circle the answer that best describes the type of soil and conditions in which your septic system drainfield is buried.

- Your septic system is installed in deep, well-drained soil (not too clayey, not too sandy) to allow full absorption and treatment of wastewater or you have a low-pressure pipe system installed in sandy soil or a pretreatment system installed in any soil.
- Your septic system drainfield is installed in deep red, clayey soil that drains reasonably well. If your soil is clayey, a handful of it easily breaks into small pieces when moist.
- Your septic system drainfield is installed in sandy soil with a shallow groundwater and does not have a low pressure or pretreatment system.
- Your septic system drainfield is installed in thin soil with hard rock, very sticky clay soils, or soil layers that restrict downward flow of water and the system does not include a pretreatment system, such as a sand filter; OR do not know.

soil layers that restrict the downward flow. Any of these conditions can keep water from flowing through the soil and cause untreated sewage to collect on the ground surface, where it can flow over to your water source.


The soil should be uniform, yellow, yellowish-red, or bright red in color, and it should not have spots of gray. Gray spots indicate that the soil may be too wet to contain enough air (anaerobic conditions) during the winter and spring.

5. Are trees and shrubs planted near your septic system?

Trees or shrubs located closer than 100 feet to septic systems may cause problems. Roots from plants sometimes enter the septic tank drainfield, the tank, or the pipes, preventing the proper working of the septic system. Failing septic systems increase the likelihood of groundwater or surface water pollution.


6. Does runoff drain away from your septic system?

To reduce water that flows through the soil where the drainfield is buried, keep the water that runs off your foundation drains, gutters, driveway, and other paved areas away from the drainfield of your septic system. Careful landscaping can help direct excess surface water away from your septic system.



Runoff draining away from the septic system

5. Circle the answer that best describes the location between your trees and your septic system.
- a. No trees are within 100 feet of your septic drainfield. You've never had a problem with roots in the drainfield, pipes, or tank.
 - b. No trees are within 50 feet of your drainfield.
 - c. The only trees within 50 feet of your septic drainfield are trees that grow poorly under wet conditions (most oaks, dogwoods).
 - d. Trees or shrubs within 50 feet of your drainfield that grow well under wet conditions (willows, willow oaks, some maples) or you've removed roots from drainfield lines at least once and make no effort to prevent root regrowth; OR do not know.



Trees should not be located too close to septic system

6. Circle the answer that best describes how surface water flows in your yard.
- a. You have landscaped the yard to divert rain water and water from your roof, gutters, and foundation drains away from the septic system.
 - b. You have landscaped the yard to divert rain water away from your septic system. You're not sure where the roof, gutters, and foundation waters drain.
 - c. You have landscaped the yard to divert rain water away from your septic system. Your roof, gutters, and foundation drain across your septic system.
 - d. Water from the roof, gutters, foundation, driveway, and yard drains over your septic system; OR do not know.

Maintenance of Your Septic System

7. How much water do you use?


As with city sewers, there are limits to the amount of water septic systems can treat. However, if you have a city sewer and use too much water, a problem occurs far away at the city sewage treatment plant. If you have a septic system and use too much water, your wastewater may backup into your yard or house, since your septic system serves as your sewage treatment plant.

The soil drainfield can support no more than 120 gallons per bedroom per day. Most people use about 50 gallons per day of water. When the amount of water entering the septic system nears design capacity, your septic system may fail.

Problems caused by using too much water can occur throughout the year, seasonally, or from time to time. For example, the soil beneath your drainfield cannot absorb as much water in the spring, when the soil is naturally more moist, as it can absorb in the summer when the soil is drier. If you wash all your laundry in one day, you may have a temporary problem caused by overloading the soil.

Reduce your water use by doing the following:

- Use 1.6 gallon (or less) per flush toilets.
- Periodically check the toilets and faucets to make sure that they are not leaking; fix immediately if they are leaking.
- Use faucet aerators at sinks and flow reducer nozzles at showers.
- Limit the length of your shower to 10 minutes or less.
- Do not fill the bathtub with more than 6 inches of water.
- Do not wash more than 1 - 2 loads of laundry per day.
- Do not use the dishwasher until it is full.



8. Do you use a garbage disposal?

To reduce the possibility of septic system failure, restrict the use of the garbage disposal unit. Garbage disposals usually double the amount of solids added to your septic tank.

7. Circle the answer that best describes the total amount of water you use in your house per day.

*Note: even if you have a well, you can have a water meter installed to measure your family's water use, or you may contact your local Cooperative Extension Service Center to get help estimating your family's water use.

- a. You use less than 35 gallons per person per day.
- b. You use between 35 and 50 gallons per person per day.
- c. You use between 50 and 60 gallons per person per day.
- d. You use more than 60 gallons per person per day, you have an in-home day care center or you take in wash for others, or your toilets or faucets have water leaks; OR do not know.

8. Circle the answer that best describes your garbage disposal.


- a. No garbage disposal.
- b. Have a garbage disposal but also have a separate tank that treats garbage disposal waste before it goes to the septic tank.
- c. Limited use of garbage disposal (3 times per week) but no separate tank.
- d. Daily use of garbage disposal and no separate tank; OR do not know.

9. Do you pour grease or oil down your sink?

Do not pour grease or cooking oils down the sink drain. Grease can harden in the drainfield and clog the soil so that no water can flow through the soil. If this happens you will need to install a new drainfield.

10. Do you use cleaning products?

Use moderate amounts of cleaning products and do not pour solvents or other poisons. Don't dispose of extra cleaning products by pouring them down the drain. Do not use toilet cleaners that are placed in the toilet tank. Such chemicals can kill the good bacteria in your septic tank and in the soil beneath your drainfield.



11. Do you dispose of solid waste materials?

Do not put items down the drain that may clog the septic tank or other parts of the system. These items include cigarette butts, sanitary napkins, tampons, condoms, disposable diapers, paper towels, egg shells, and coffee grounds. Do not use your toilet for disposal of facial tissues. This adds extra solids and water to the septic system.

9. Circle the answer that best describes how you dispose of your grease and oil.

- a. No disposal of grease and oil down the drain, and oil and grease wiped from cooking items with a paper towel before washing.
- b. Limited rinsing of grease and oil while cleaning cooking items during special occasions (holidays, or when entertaining).
- c. Routine rinsing of grease and oil down the drain when cleaning cooking items.
- d. Routine disposal of grease and oil down the drain from cooking pans, fryers, etc.; OR do not know.

10. Circle the answer that best describes your use of household cleaning products and how you dispose of solvents and poisons.

- a. Minimal use of household chemicals (only 2 cups per week). No disposal of harmful chemicals such as solvents, paints, thinners, disinfectants, pesticides, poisons, and other substances that can kill the bacteria in the tank and soil.
- b. Careful use of household chemicals only when needed to unclog pipes, clean fixtures, etc.
- c. Daily use of household chemicals, such as degreasers, pipe decloggers or toilet bowl sanitizers.
- d. Excessive amounts of cleaning agents poured down the drain or periodic disposal of solvents and other substances such as paints, paint thinners, poisons that can kill the bacteria in the tank and soil or pollute the groundwater; OR do not know.

DO NOT FLUSH

coffee grounds
dental floss
disposable diapers
kitty litter
sanitary napkins
tampons
cigarette butts
condoms
paper towels
facial tissues



12. Does all your wastewater drain into your septic system?

Make sure that all wastewater produced in the house is directed into the septic system. This includes not only the wastewater from the kitchen sink and the toilets, but also wastewater from tubs, showers, and laundry facilities.

13. Have you protected your septic system from physical damage?

To protect your septic system from physical damage:

- Keep the soil over the drainfield covered with grass to prevent soil erosion.
- Be careful not to mow the lateral turn-ups if you have a special type of septic system called a “low-pressure pipe system.”
- Don’t drive over the system.
- Maintain the natural shape of the land immediately downslope of the system. Protect this area from cutting and filling.
- Do not build over the drainfield area.

14. Have you built over your drainfield?

Do not cover the tank or drainfield with asphalt or concrete. Do not build any additions to your house over the drainfield without first checking with your local health department. For proper function and maintenance, your entire septic system must be accessible. Use a property layout sketch to help you place new facilities on your property away from the septic system.

11. Circle the answer that best describes how you dispose of solid products.


- a. You never use your septic system as a trash can for any solid products such as cigarette butts, tissues, sanitary napkins, tampons, condoms, cotton swabs, cat litter, coffee grounds, or disposable diapers.
- b. You occasionally (once or twice yearly) use your septic system as a trash can for cigarette butts, tissues, sanitary napkins, tampons, condoms, cotton swabs, cat litter, coffee grounds, or disposable diapers.
- c. You use your septic system every month as a trash can for cigarette butts, tissues, sanitary napkins, tampons, condoms, cotton swabs, cat litter, coffee grounds, or disposable diapers.
- d. You use your septic system every week as a trash can for cigarette butts, tissues, sanitary napkins, tampons, condoms, cotton swabs, cat litter, coffee grounds, or disposable diapers; OR do not know.

12. Circle the answer that best describes how you dispose of wastewater.

- a. All of your wastewater is disposed of in an approved septic system.
- b. All of your wastewater is disposed of in a septic system that was installed before state regulations went into effect but seems to be working okay.
- c. Some of your wastewater, such as wash water or kitchen wastewater, goes to a separate pipe that discharges into a ditch or dry well or in the woods.
- d. All of your wastewater goes to a pipe that discharges into a ditch or dry well or in the woods; OR do not know.

13. Circle the answer that best describes vehicular traffic over the septic system.

- a. No vehicles or farm equipment are ever driven over your septic tank or drainfield, except lawnmowers.
- b. You have carefully (once or twice) driven a car over your drainfield, but don't cross it with heavy farm equipment and have never driven over the tank or pipe network.
- c. You have periodically driven vehicles over your drainfield, but don't ever cross it with heavy farm equipment.
- d. You have driven over your septic tank or pipe network with vehicles or over any part of the system with heavy farm equipment, trucks, etc.; OR do not know.



Your local health department should be able to tell you the size of your tank. Then, using the table below, determine how often your tank should be pumped. For example, if there are 4 people living in your house and your septic tank can hold 1,000 gallons, the tank should be inspected and pumped at least every three years.

Time Table for Inspecting and Pumping Your Septic Tank (in years)					
— — — Number of People Using the System — — —					
Tank Size (gallons)	1	2	4	6	8
Number of Years					
900	11	5	2	1	<1
1,000	12	6	3	2	1
1,250	16	8	3	2	1
1,500	19	9	4	3	2

Source: Adapted from "Estimated Septic Tank Pumping Frequency," by Karen Mancl. 1984. *Journal of Environmental Engineering*. Volume 110.

17. Do you have easy access to your septic system?

It is important to know the location of your septic system. It is also important to be able to check your septic system. Easy access to your septic system through an access riser allows it to be inspected and cleaned. The following diagram illustrates an access riser.



18. Have you hired a certified septic system operator?

Hire a certified operator when you have a system that uses a pump including the following:

- Low-pressure pipe system
- Pump-to-conventional system
- Pressure manifold system
- Mechanical aerobic treatment unit (ATU)
- Drip irrigation system

This operator will check the overall performance of your system and the operation of the pump, electrical controls, and alarm on a regular basis. Hiring a certified operator will cost some money, but can provide you with professional care for your septic system.

You are required by state law to hire a certified subsurface system operator if you have a low-pressure pipe system that was installed or repaired after July 1, 1992, or if you have an aerobic treatment unit (ATU).

16. Circle the answer that best describes how often your septic tank is cleaned.

- a. You have your septic tank inspected and pumped as scheduled in the table at left.
- b. You have septic tank scum and sludge levels checked each year and your septic tank pumped out as needed.
- c. You have scum and sludge levels checked and your tank pumped out about once every 5-10 years.
- d. It has been more than 5-10 years since you've had your septic tank checked and pumped out or you've never pumped out your septic tank, or you don't know if it has ever been pumped out; OR do not know.



17. Circle the answer that best describes your access to your septic tank.

- a. You have a concrete riser or manhole over your septic tank that provides easy access to the tank.
- b. You do not have a concrete riser, but the location of your tank is marked and the tank is less than six inches deep.
- c. You do not have a concrete riser, but the location of your tank is marked. The top of your tank is more than six inches deep.
- d. You do not know where your tank is located; OR do not know.



18. Circle the answer that best describes how you use a certified subsurface system operator if you have one of these four special types of septic systems: a pump-to-conventional, pressure manifold, low-pressure pipe system, or ATU system.

- a. You have hired a certified subsurface system operator if you have a pump-to-conventional, pressure manifold, or low-pressure pipe system.
- b. Not Applicable
- c. Not Applicable
- d. You have not hired a certified subsurface system operator to help operate and maintain your pump-to-conventional, pressure manifold, low-pressure pipe system, or ATU system; OR do not know.

19. Have you talked to a certified septic system operator?

Hiring a certified operator to inspect your pump system is important. It is also important to talk to your certified operator to find out what you should do to maintain your septic system between visits.

20. Are your drainage ditches maintained?

For septic systems that use ditches or subsurface drain tiles to drain excess water from the soil, it is important that the outlets from these ditches be cleaned. If the outlet becomes plugged up, water can no longer drain from the soil into the ditch. The soil will stay too wet for the drainfield to work properly and your septic system may fail.

For more information:

You must receive a permit from your local health department before installing or repairing any septic system.

Your county health department can be a valuable source of information on the following topics:

- Site selection and construction of septic systems
- Septic system inspection and maintenance
- List of registered septic system installers
- Construction records for existing septic systems
- Information on systems that legally require a certified subsurface system operator

Related publications available from the Cooperative Extension Service:

- *About Septic Systems: What You Need to Know*
- *Septic System Owner's Guide*, AG-439-22
- *Soil Facts: Septic Systems and Their Maintenance*, AG-439-13
- *Soil Facts: Investigate Before You Invest*, AG-439-12
- *Soil Facts: Management of Single Family and Small Community Wastewater Treatment and Disposal Systems*, AG-439-11

The publications listed above are available at your county Cooperative Extension Service Center. You may also order these publications from Communication Services, Campus Box 7603, North Carolina State University, Raleigh, NC 27695-7603.

19. Circle the answer that best describes how you obtain information from your certified operator about your septic system if you have a pump system.

- a. You find out from your operator what you should be doing between visits to help the system work properly.
- b. You do not discuss your system with your certified operator but do let him/her know immediately if the alarm is activated.
- c. You turn off the alarm when it is activated, hope the problem goes away until the next scheduled visit by your certified operator.
- d. You have a pump system, but have not hired a certified operator to help you manage the system; OR do not know.



20. If you use drainage ditches, circle the answer that best describes how you maintain your drainage ditches.

- a. Your drainage ditches and outlets are maintained on your property and on surrounding properties.
- b. Your drainage ditches are well maintained on your property but not on surrounding properties.
- c. Your drainage ditch still exists but is beginning to become filled with soil or with trees, or brush growing in it or your drainage outlet is partially covered by water, soil, or debris.
- d. The outlet of your drainage ditch is blocked or your drainage ditches have filled in and water is not flowing freely through them; OR do not know.

WARNING

NEVER enter a septic tank.

The following publication is available from the North Carolina Department of Environment, Health and Natural Resources, Department of Environmental Health (919/733-5083):

- *On-Site Wastewater Management Guidance Manual*, 1996.



College of Agriculture & Life Sciences · NC State University
School of Agriculture and Environmental and Allied Sciences ·
NC A&T State University

Prepared by

Deanna L. Osmond
Water Quality Extension Specialist

Michael T. Hoover
Extension Soil Science Specialist

Wilma S. Hammet
Extension Home Furnishing Specialist

Janet Young
Layout and Design Specialist


The concept for these materials was adapted from materials produced by the National Farm*A*Syst Program, University of Wisconsin, Madison, WI.

North Carolina's Farm*A*Syst and Home*A*Syst Program is coordinated by Deanna L. Osmond, North Carolina State University. Technical editing was provided by Judith A. Gale, and copy editing by Cathy Akroyd. Michael J. Vepraskas, Aziz Amoozegar, and Stanley W. Buol were the technical reviewers at North Carolina State University. Technical review was also provided by the North Carolina Department of Environment, Health, and Natural Resources. Technical review was also provided by the following people within the North Carolina Department of Environment, Health and Natural Resources: Debra Owen, Environmental Services Branch, Environmental Biologist; Dennis Ramsey, Assistant Chief of Operations Branch; and Steven J. Steinbeck, Head, On-Site Wastewater Services Branch, On-Site Wastewater Section, Division of Environmental Health.

This project has been funded with Section 319 grant monies from the U.S. Environmental Protection Agency through the N.C. Department of Environment and Natural Resources, Division of Water Quality.

Published by

NORTH CAROLINA COOPERATIVE EXTENSION SERVICE



Soil Facts

Why Do Septic Systems Fail?

A properly designed, constructed, and maintained septic system should treat and disperse wastewater effectively for many years. Unfortunately, septic systems sometimes fail.

Is My Septic System Failing?

How do you know if your septic system is failing? First, answer the following questions:

1. Do your drains empty slowly for reasons other than old, clogged pipes?
2. Does sewage back up into your house?
3. Have you noticed a wet, smelly spot in your yard?
4. Is your septic tank piped to a ditch or stream?
5. Is your washing machine or sink piped to a road or stream?
6. When it rains or the ground is wet, do you experience problems with your drains?
7. When you do laundry, does a wet spot appear in your yard?
8. Do you frequently have to pump your septic tank (more than once a year)?
9. Is the grass over or around your septic tank greener than the rest of your lawn?
10. Is the area around your septic tank or drainfield wet or spongy even when it has not rained for a week or more?

If you answered “yes” to any of these questions, your septic system has failed or is near failing. This means that it is not treating and disposing of sewage in a safe, environmentally sound fashion. You may also be able to tell your system is in trouble if noxious bacteria (fecal coliform) or large amounts of nutrients (particularly ammonia) are found in both nearby wells and surface water.




Figure 1. Wastewater treatment and dispersal in the environment (not to scale).

Distributed in furtherance of the Acts of Congress of May 8 and June 30, 1914. North Carolina State University and North Carolina A&T State University commit themselves to positive action to secure equal opportunity regardless of race, color, creed, national origin, religion, sex, age, or disability. In addition, the two Universities welcome all persons without regard to sexual orientation. North Carolina State University, North Carolina A&T State University, U.S. Department of Agriculture, and local governments cooperating.

What Is a Septic System?

A septic system consists of four basic components: the source (home), the septic tank, the drainfield or leach field, and the soil beneath the drainfield (Hoover, 2004; Figure 1). Several different septic system designs are used in North Carolina. The type of system used is based on the lot's soil and site conditions; however, the conventional system (as illustrated in Figure 1) is the most commonly used in the state.

Excessive Water Use

A common reason for septic system failure is overloading the system with more water than it can absorb. A septic system is designed for a specific wastewater flow rate based on the number of bedrooms (120 gallons per bedroom per day) in the house served by the system. When this flow rate is exceeded, the excess water backs up into the house or surfaces in the yard. This problem is often the result of a leaky fixture: either a toilet that has a slow leak or a dripping faucet. A change in water use, such as more people in the house or the addition of a water-using appliance, such as a dishwasher or washing machine, may add additional water to your septic system. Further problems can arise if a sump pump, icemaker, or dehumidifier drains into the septic tank. Each of these devices can add excess water and should not be connected into your septic system.

Along with excess water from inside the house, drainage or runoff water outside also may overload the septic system. In particular, water from roofs, roads, or paved areas may be diverted onto the system drainfield. This surface water will saturate the soil to the point that it can no longer absorb additional water. The result is sewage backing up into the house or on top of the ground. Finally, if the groundwater or surface water is allowed to enter the septic tank, it, too, can overload the system. For this reason, septic tanks are designed to be

watertight, and surface water should be diverted from the access covers of the septic tank.

Poor Maintenance or None at All

As with all major appliances, septic systems require routine maintenance. The N.C. Cooperative Extension publications *Septic Systems and Their Maintenance*, AG-439-13, and *Septic System Owner's Guide*, AG-439-22, describe the proper maintenance of a septic system. The main purpose of the septic tank is to stop solids from entering into the drainfield. If solids do reach the drainfield, they will clog the small spaces or pores in the gravel and soil below, resulting in sewage backing up into the house or surfacing in the yard. The lack of septic tank maintenance is a key cause of premature septic system failure. You should have your tank pumped every 3 to 5 years depending on use (see *Septic Systems and Their Maintenance* (AG-439-13) for specific guidance on pumping frequency). Also, you should have the septic tank pumper inspect the sanitary tee outlet or effluent filter to ensure proper function. Houses with septic systems should not have a garbage disposal. But if your home has a garbage disposal or grinder pump, the tank should be pumped more frequently. Additives, whether biological or chemical, have not been shown to have any beneficial effect on the solids in the tanks or system in general. For this reason, they are not recommended.

If your system received its permit from your county health department after January 1, 1999, it must have an effluent filter. These filters are designed to prevent finer solids from reaching the drainfield. The filters require some additional maintenance. As the filters clog with solids, your drains may work more slowly. When this occurs, a septic tank pumper or the homeowner can clean the filter with a garden hose, making sure the waste on the filter is washed off into the inlet side of the tank, and replace

the filter in the tank. If the filter is clogged, it is often a sign that the tank needs to be pumped.

Poor Design and Installation

An improperly designed septic system is a failure waiting to happen. It is critical that the system be designed with adequate space and has suitable soil. The space requirements are determined by the amount of sewage flowing into the system and by the soil and site conditions of the drainfield. In designing a septic system, it is assumed that there are two people per bedroom in a house and that each resident produces about 60 gallons of wastewater a day. Therefore, a septic system is designed to handle a flow rate of 120 gallons per day per bedroom (two people per bedroom x 60 gallons per person per day). For non-residential property, the flow rate is determined by the proposed use. Soil and site conditions dictate the amount of sewage that can be safely applied to the soil. In general, sandy soils can accept more wastewater than clayey soils, which results in smaller drainfields for sandier soils. Finally, the location of a seasonal high water table or a restrictive layer (such as hard pan or rock) determines the depth below the soil surface that the bottom of the drainfield trenches can be placed.

The soil is the most important part of the septic system in treating and ultimately dispersing the treated sewage. If the soil beneath the drainfield is too wet, the sewage may not be adequately treated before it reaches groundwater. Furthermore, if a restrictive layer is too close to the trench bottom, the soil may not be able to absorb all of the sewage, thus forcing it to the surface or back up into the house. In North Carolina, there must be 12 to 18 inches of unsaturated soil beneath the drainfield trench bottom. This distance is referred to as the vertical separation distance. Environmental health specialists employed by the county or district health departments are trained to evaluate the soil and site to ensure that it is suitable for sewage treatment

and dispersal. Additional information can be obtained in the N.C. Cooperative Extension publication *Investigate before You Invest* (AG-439-12).

Even when a system is designed properly given the flow rate and soil and site conditions, problems can result from the construction and installation of the system. When systems are installed in soil that is too wet, the soil is significantly compacted and the soil pore space is smeared in excavated areas. In extreme cases this can seal the soil in the trenches, not allowing any wastewater to flow into the underlying soil for treatment and dispersal. With the reduced capacity for wastewater to flow into the soil, it is likely that the wastewater will back up into the house or emerge on top of the ground.

Septic systems must be installed according to the design. This includes checking the elevation of each component. If the trench bottoms, drain lines, or distribution box are not level, wastewater may not flow properly or be distributed evenly across the drainfield. Step-downs or other devices used on sloping sites must be properly installed, or one trench may be overloaded with wastewater. Interceptor drains or other drainage systems must have an outlet that allows groundwater to drain away from the drainfield. Finally, the soil cover over the drain-

field should be uniform and crowned to prevent surface water from ponding on or flowing into the trenches. If the area is landscaped, use small, lightweight equipment because heavy machinery may compact the soil and even crush the pipes or septic tank.

Physical Damage

Driving, paving, or building on top of a septic system can damage or destroy it. The pipes and septic tank can shift position or be crushed from repeated or even occasional abuse. Furthermore, the soil can be compacted, or ruts may form, exposing system components and possibly untreated sewage to the ground surface. Paving over all or a portion of the drainfield may prevent air from getting into the soil, as well as limit access for repairs or maintenance. Building over the drainfield may cause compaction or even damage a line due to the weight of the structure or the location of building footings. Paving or building over the septic tank also will prevent required tank maintenance.

Tree roots may clog the drain lines and gravel in the trenches. The best way to prevent this from occurring is to remove or simply not plant trees or shrubs within 25 feet of the drainfield. Roots may also get into the septic tank or distribution box, so do not plant trees and shrubs over these

devices. You should plant grass over the drainfield and all other outdoor system components. The grass aids in removal of water and helps to prevent soil from eroding over the components.

Most septic systems require that an area be set aside for possible repairs. This area should be treated and protected just as if it were currently in use.

Repairing a Failing Septic System

Septic systems may fail despite proper maintenance, design, and construction. If properly maintained, the life span of a septic system is similar to that of an asphalt shingled roof. If a failure does occur, the problem needs to be corrected swiftly and properly. Any failure, despite its cause, poses a nuisance, presents a public health hazard, and can degrade the environment.

If your system is failing or you suspect a failure, contact your local environmental health department. The department will send an environmental health specialist trained in assessing failing septic systems to determine the cause or causes of the failure and suggest how to repair the problem. Do not attempt to fix the failure without the approval of the local environmen-

Dos and Don'ts for Septic System Repairs

1. **Do** report problems to your local environmental health department and ask for an evaluation.
2. **Do** conserve water until a repair is made.
3. **Do** rope or fence off the area where sewage is on the ground surface to keep people and animals away from untreated sewage.
4. **Don't** place more soil over a wet smelly spot, which is probably where raw sewage has leaked. This will not solve the problem and may cause sewage to back up into your house. Raw sewage contains harmful bacteria that may cause sickness or death.
5. **Don't** pipe or ditch the sewage to a ditch, storm sewer, stream, sinkhole, or drain tile. This will pollute surface water, groundwater, or both, and cause a health hazard. **It is illegal.**
6. **Don't** pipe, ditch, or run the sewage into an abandoned well or other hole in the ground. This will pollute groundwater and cause a health hazard. **It is illegal.**
7. **Don't** ignore the problem. It will not go away. The longer you wait to fix the problem, the worse the situation may become, possibly making a simple repair into a very costly one.

tal health department. In some cases, the corrective measures could be as simple as installing water conservation devices. In the case of a complete system failure, construction of a new septic system may be the only solution.

Preventing Failures

Regular maintenance of your septic system is the best way to prevent a failure. As stated, the N.C. Cooperative Extension publications *Septic Systems and Their Maintenance* (AG-439-13) and *Septic System Owner's Guide* (AG-439-22) describe the proper maintenance of a septic system. Listed are some of the things you can do.

1. **Conserve water.** Use water-saving fixtures and conserve water in the kitchen, bath, and laundry to reduce the amount of wastewater the soil has to absorb. This is especially beneficial immediately after a heavy rain as well as during the winter and early spring.

2. **Repair or replace leaky fixtures.** Leaky fixtures add excess water to the drainfield, so fixing them promptly will reduce the amount of water the soil has to absorb.

3. **Maintain proper cover and landscape over the drainfield.** Make sure the drainfield is covered well with grass to prevent soil erosion. A crowned drainfield and surface swales will prevent excess surface water from entering the trench. Also, make certain that gutters, downspouts, patios, walkways, and driveways do not divert water over the drainfield or septic tank.

4. **Pump your tank regularly.** Regular pumping prevents solids from reaching the drainfield and causing it to clog. The tank should be pumped every 3 to 5 years depending on use. Additives have not been shown to significantly reduce the amount of solids in the tank. Do not use them in place of

regular septic tank pumping.

5. **Limit what goes into the septic tank.** Do not dispose of chemicals, solvents, cleaning fluids, paint, motor oil, gasoline, and other such substances in the septic tank. They may kill all the beneficial bacteria in the tank and soil as well as pollute the environment. Dispose of these materials properly at your local recycling center or transfer station. Kitty litter, hygiene products, cooking oil, grease, and waste food may clog the system and should be disposed of in the trash. Waste from fruits and vegetables can be composted.

6. **Do not drive or build over any part of your septic system.**

7. **Inspect the system components routinely.** Check for signs of problems that can be corrected before a failure occurs.

References

- U. S. EPA. 1997, April. Response to Congress on Use of Decentralized Wastewater Treatment Systems, EPA 832-R-97-001b. Washington, DC: U.S. EPA, Office of Water.
- Hoover, M. T. 1990. *Soil Facts: Investigate Before You Invest*. North Carolina Cooperative Extension Service, No. AG-439-12. Raleigh: NC State University. Online: <http://www.soil.ncsu.edu/publications/Soilfacts/AG-439-13.pdf/>
- Hoover, M. T. and T. Konsler. 2004. *Soil Facts: Septic Systems and Their Maintenance*. North Carolina Cooperative Extension Service, No. AG-439-13. Raleigh: NC State University. Online: <http://www.soil.ncsu.edu/publications/Soilfacts/AG-439-13/>
- Hoover, M. T. and W. S. Hammet. 2004. *Soil Facts: Septic System Owner's Guide*. North Carolina Cooperative Extension Service, No. AG-439-22. Raleigh: NC State University. Online: <http://www.soil.ncsu.edu/publications/Soilfacts/AG-439-22.pdf/>
- Hoover, M. T., R. Rubin, and F. Humenik. 1998. *Choices for Communities: Wastewater Management Options for Rural Areas*. North Carolina Cooperative Extension Service. No. AG-585. Raleigh: NC State University.
- Tyler, E. J., R. Laak, E. McCoy, and S. S. Sandhu. 1977. *The Soil as A Treatment System*. In *Home Sewage Treatment*, ASAE no. 5-77. St. Joseph, MI: American Society of Agricultural Engineers

Prepared by

David L. Lindbo, Associate Professor and Soil Extension Specialist, Department of Soil Science

Diana Rashash, Area Environmental Education Specialist, NC Cooperative Extension

Michael T. Hoover, Professor and Soil Extension Specialist, Department of Soil Science

Adapted from Ohio, Michigan, and Kansas Cooperative Extension Service publications

For more information, contact your local health department or county Cooperative Extension Service Center.

6,000 copies of this public document were printed at a cost of \$780.81 or \$0.13 each.

© 2005 North Carolina State University

Published by

NORTH CAROLINA COOPERATIVE EXTENSION

ATTACHMENT 4: Pictures



Septic Tank Location



Outlet Compartment



Inlet Compartment



Drainfield Area



Drainfield Area



Inlet Pipe



Camera Inspection of Drainfield Line



Baffle Wall