

ACCOUNT NUMBER

MERCHANT NUMBER

BUYER NAME

MERCHANT NAME / MERCHANT ADDRESS

Promotional Offers - See reverse side for additional details - APR refers to Annual Percentage Rate

- ☒ 600 Reduced 9.99% APR and fixed monthly payments equal to 1.25% of promo purchase amount - Until Paid in Full
- ☐ 604 Reduced 7.99% APR and fixed monthly payments equal to 2.00% of promo purchase amount - Until Paid in Full
- ☐ 602 Reduced 5.99% APR and fixed monthly payments equal to 3.00% of promo purchase amount - Until Paid in Full
- ☐ 605 No Monthly Interest if Paid in Full within 18 Months (Deferred Interest) 2.6 9.9 % APR ☐ Check if Variable -- If variable, APR varies with the market based on the Prime Rate.

No Monthly Interest Charges will be assessed if the promotional purchase balance is paid in full within the promo period. If the promo purchase balance is not paid in full by the end of the promo period, interest will be imposed from the date of purchase at the APR inserted immediately above. Fixed monthly payments are required equal to 2.50% of the highest balance applicable to this promo purchase, rounded to the next highest whole dollar, until paid in full.

CH Buyer(s) Initial: I have reviewed and selected the promotional option that meets my needs.

DESCRIPTION			
☐ BATH REFACE/WALK IN TUBS	☐ HVAC	☐ PLUMBING	☐ SPA
☐ ELECTRIC	☐ INSULATION	☐ ROOFING	☐ WINDOWS/DOORS
☒ GENERATOR	☐ KITCHEN REFACE	☐ SIDING	☐ OTHER _____
☐ GUTTER SYSTEM	☐ PAVERS/LANDSCAPING	☐ SOLAR	
Brand / Description <u>GENERATOR</u>		SALE PRICE <u>11515.48</u>	
Model # / Description _____		_____	
Brand / Description _____		_____	
Model # / Description _____		_____	
Includes any and all payments made by and on behalf of the Buyer. This form is for final payment and cannot be processed until the contract between the Buyer and Merchant has been completed.		TOTAL PRICE	<u>11515.48</u>
		ADVANCED PAYMENTS	_____
		AMOUNT FINANCED	<u>11515.48</u>

AUTH. CODE

10/07/2020

DATE OF SALE

I acknowledge receipt of a completed copy of this Sales Slip and have reviewed and understand the promotional terms that will apply to this purchase. I authorize the amount shown to be charged to my credit card account shown above and agree that the purchase will be governed by the terms of the Synchrony Bank Credit Card Agreement.

If this was an in-home sales transaction, I acknowledge that I have been provided by the Merchant with both the oral and written notice of my right, as a Buyer, to cancel this transaction (if applicable).

Synchrony Bank assesses a one-time \$29 Activation Fee under the Credit Card Agreement at the time the first purchase posts to the account. Any additional surcharges or fees charged by the merchant in connection with applying for or using the Credit Card are prohibited.

CH
(BUYER SIGNATURE)

X
(BUYER SIGNATURE)

DEALER/SYNCHRONY BANK

202-343-00 (5/2019) HI-B 38302C

48531



**Crawford****Crawford & Company**

5335 Triangle Parkway NW

Peachtree Corners, GA 30092-6500

Tel: 919-623-9283 Fax: 866-296-3187

E-mail: Shelby_Lary@us.crawco.com

CONTINUED - Roofl

DESCRIPTION	QUANTITY	UNIT PRICE	TAX	RCV	DEPREC.	ACV
-------------	----------	------------	-----	-----	---------	-----

Not present on the roof during inspection; required by International Residential Code and/or North Carolina Residential Code. Allowed under Law and Ordinance coverage. Code cited below:

2018 North Carolina Residential Code R905.1.2 Ice barriers. In areas where the average daily temperature in January is 25° F (- 4° C) or less or when Table R301.2(1) criteria so designates, an ice barrier shall be installed for asphalt shingles, metal roof shingles, mineral-surfaced roll roofing, slate and slate-type shingles, wood shingles and wood shakes. The ice barrier shall consist of not fewer than two layers of underlayment cemented together, or a self-adhering polymer modified bitumen sheet shall be used in place of normal underlayment and extend from the lowest edges of all roof surfaces to a point not less than 24 inches (610 mm) inside the exterior wall line of the building. On roofs with slope equal to or greater than 8 units vertical in 12 units horizontal, the ice barrier shall also be applied not less than 36 inches (914 mm) measured along the roof slope from the eave edge of the building.

Exception: Detached accessory structures not containing conditioned floor area.

2018 North Carolina Residential Code R905.2.8.2. Valleys. For closed valleys (valley covered with shingles), valley lining of one ply of smooth roll roofing complying with ASTM D 6380 and not less than 36 inches wide (914 mm) or valley lining as described in Item 1 or 2 shall be permitted. Self-adhering polymer modified bitumen underlayment complying with ASTM D 1970 shall be permitted in lieu of the lining material.

14. Step flashing 45.00 LF 8.40 25.52 403.52 (172.94) 230.58

2015 International Residential Code R908.5 Reinstallation of materials. Any existing flashing, edging, outlets, vents or similar devices that are a part of the roof assembly shall be replaced where rusted, damaged or deteriorated. .

15. R&R Flashing - L flashing - galvanized 7.00 LF 5.03 2.06 37.27 (13.99) 23.28

2015 International Residential Code R908.5 Reinstallation of materials. Any existing flashing, edging, outlets, vents or similar devices that are a part of the roof assembly shall be replaced where rusted, damaged or deteriorated. .

Totals: Roofl 1,058.70 23,234.33 6,542.02 16,692.31

Total: Roof 1,058.70 23,234.33 6,542.02 16,692.31

Main Level**Bedroom Closet****Height: 7' 1"**

220.57 SF Walls
283.19 SF Walls & Ceiling
6.96 SY Flooring
33.65 LF Ceil. Perimeter

62.61 SF Ceiling
62.61 SF Floor
30.98 LF Floor Perimeter

Door**2' 8" X 6' 8"****Opens into Exterior**

DESCRIPTION	QUANTITY	UNIT PRICE	TAX	RCV	DEPREC.	ACV
-------------	----------	------------	-----	-----	---------	-----

16. Haul debris - per pickup truck load - including dump fees 1.00 EA 147.46 0.00 147.46 (0.00) 147.46
interior repairs only

10/31/2021

Page: 3



TRUAX_COLLEEN1

JOB_5255037

Dwelling

Roof

Roof1

3589.15 Surface Area
347.36 Total Perimeter Length
13.72 Total Hip Length

35.89 Number of Squares
107.11 Total Ridge Length

DESCRIPTION	QUANTITY	UNIT PRICE	TAX	RCV	DEPREC.	ACV
E-ROOFING						
Remove Laminated - comp. shingle rfg. - w/ felt	36.44 SQ	118.08	0.00	4,302.84	(0.00)	4,302.84
Laminated - comp. shingle rfg. - w/ felt	39.00 SQ	232.24	611.37	9,668.73	(4,834.37)	4,834.36
Remove Additional charge for steep roof - 10/12 - 12/12 slope	34.47 SQ	51.77	0.00	1,784.51	(0.00)	1,784.51
Additional charge for steep roof - 10/12 - 12/12 slope	36.88 SQ	59.63	148.44	2,347.59	(0.00)	2,347.59
R&R Ridge cap - composition shingles	105.00 LF	5.99	26.01	654.96	(246.82)	408.14
R&R Continuous ridge vent - shingle-over style	105.00 LF	9.85	63.01	1,097.26	(427.05)	670.21
R&R Flashing - pipe jack	3.00 EA	55.84	9.69	177.21	(65.67)	111.54
R&R Gable cornice return - 3 tab - 2 stories or greater	2.00 EA	96.20	10.90	203.30	(103.40)	99.90
Gutter guard/screen - High grade - Detach & reset unless metal gutter guard mechanically attached	151.00 LF	7.56	77.06	1,218.62	(0.00)	1,218.62
Drip edge/gutter apron installed on the front eaves w/ high-grade gutter guard	151.00 LF	2.48	25.28	399.76	(171.32)	228.44
Drip edge installed on the back eave	165.00 LF	2.37	26.40	417.45	(178.90)	238.55
DE UPGRADES						
Asphalt starter - universal starter course present on the roof during inspection; required by International Residential Code and/or North Carolina Residential Code. Allowed under Law Ordinance coverage. Code cited below:	151.00 LF	1.66	16.92	267.58	(200.69)	66.89
8 North Carolina Residential Code R905.1 Roof Covering Application. Roofing coverings shall be applied in accordance with the applicable provisions of this section and the manufacturer's installation instructions. Unless otherwise specified in this section, roof coverings shall be installed to resist the component and cladding loads specified in Table R301.2(2), adjusted for height and exposure in accordance with Table R301.2(3). er Manufacturer, the use of a cut-up strip shingle as the "starter" course is not recommended. Cut-up shingles may not have properly bonded adhesive adequate to resist the component and cladding loads specified in Table R301.2(2).						
Water barrier	171.00 SF	1.39	16.04	253.73	(126.87)	126.86